

Optix Linear Surface 1200 Direct SylSmart
OPTIX LINEAR SURFACE 1200 4000K ALU SSC EM
2023805







PRODUCT OVERVIEW

Product name	OPTIX LINEAR SURFACE 1200 4000K ALU SSC EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	3400
Luminaire efficacy (lm/W)	113
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 19
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	85
Total power consumption (W)	30
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238057

PHOTOMETRY

Optix Linear Surface 1200 Direct SylSmart
OPTIX LINEAR SURFACE 1200 4000K ALU SSC EM
2023805



TECHNICAL DRAWINGS

