



Features

• Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 4800lm; 32W; 150lm/W; 4000K; SDCM<5; CRI80; IP66; IK08 (sensor IK03); Class I; 69,000hrs (L80B20) lifespan; 1293mm x 87mm x 80mm; D-mark; SylSmart Connected Industry enabled.


Product Overview

Product name	Resisto 1200 HE IP65 4800lm 840 SSE
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
Fixture luminous flux (lm)	4800
Luminaire efficacy (lm/W)	150
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 24
Photobiological Risk Group	RG1
Total power consumption (W)	32
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey


Resisto 1200 HE IP65 4800lm 840 SSE
0010239

IP rating	IP65
IK rating	IK08
Product EAN number	5410288102399
Warranty	5 years

Photometry



Technical drawings



Resisto 1200 HE IP65 4800lm 840 SSE
0010239

Data table

GENERAL DATA

Product name	Resisto 1200 HE IP65 4800lm 840 SSE
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	4800
Luminaire efficacy (lm/W)	150
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 24
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	32
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	350
Inrush Current (A)	18

Resisto 1200 HE IP65 4800lm 840 SSE 0010239

Inrush Duration (µs)	200
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	69000
Lifespan L90 B10	31000

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK08
IK rating of sensor	IK03
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1293
Nominal Product Width (mm)	87
Weight (kg)	1.76

PACKAGING

Single packaging type	Carton
Product EAN number	5410288102399
Packaging single width (cm)	10.0
Packaging single depth (cm)	8.5
DUN14 (outer)	05410288102399
Packaging outer length / height (cm)	120.5

SAFETY DATA

Optimal operating condition (°C)	-20-40
----------------------------------	--------



Resisto 1200 HE IP65 4800lm 840 SSE
0010239

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No