

Optix Linear Surface 1200 Direct-Indirect
OPTIX LINEAR SURFACE 1200 D/I 4000K ALU DALI
2023811




PRODUCT OVERVIEW

Product name	OPTIX LINEAR SURFACE 1200 D/I 4000K ALU DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	4500
Luminaire efficacy (lm/W)	145
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	31
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238118

PHOTOMETRY

Optix Linear Surface 1200 Direct-Indirect
OPTIX LINEAR SURFACE 1200 D/I 4000K ALU DALI
2023811



Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	0.75	37.9°	960
0.5	0.75	35.0°	1717
0.5	0.75	35.0°	1728
1.0	1.50	37.9°	240
1.0	1.50	35.0°	429
1.0	1.50	35.0°	431
1.5	2.25	37.9°	160
1.5	2.25	35.0°	191
1.5	2.25	35.0°	192
2.0	3.00	37.9°	90
2.0	3.00	35.0°	107
2.0	3.00	35.0°	108
2.5	3.75	37.9°	58
2.5	3.75	35.0°	69
2.5	3.75	35.0°	69
3.0	4.50	37.9°	40
3.0	4.50	35.0°	48
3.0	4.50	35.0°	48

TECHNICAL DRAWINGS

