



## PHOTOMETRIC LIGHT REPORT

# Track spot | 48V | linear | black | 8W | 3000K | 100° | DALI

Article number: 168-167



Go to the  
webshop  
of Tronix  
Lighting



**TRONIX**



168-167 Track spot | 48V | linear | black | 8W | 3000K | 100° | DALI

## Introduction

### Purpose of this Document

This document provides accurate and objective photometric data for Tronix Lighting item 168-167. All information is based on actual measurements taken from standard production units. No modifications were made to enhance performance results. In some cases, minor adjustments—such as temporary removal of covers, cables, or mounting features—were necessary for testing purposes. These did not influence product performance.

### Test Methodology

Testing was conducted using randomly selected, unopened samples from regular inventory. All tests comply with the LM-79-19 standard, the recognized method for photometric and electrical measurements of LED and OLED luminaires. This standard, an update of IES LM-79-2008, outlines environmental test conditions, stabilization procedures, measurement methods, and approved instruments. It uses absolute photometry, meaning results directly reflect the performance of the tested product, without comparison to rated lamp standards.

### Product 168-167 was tested using:

- A photogoniometer to measure luminous intensity distribution at various angles
- An integrating sphere to determine total luminous flux and colour characteristics

### Compliance & Certification

Item 168-167 meets the requirements of the following EU directives. Tronix Lighting certifies that all relevant tests were executed in accordance with the applicable standards, and the CE mark is applied accordingly:

- General Product Safety – Directive 2023/988/EC
- Low Voltage Directive (LVD) – Directive 2014/35/EU
- Electromagnetic Compatibility (EMC) – Directive 2004/108/EC
- Ecodesign – Directive 2009/125/EC
- RoHS 3 – Directive 2011/65/EU + Amendment 2015/863/EU

### Recycling & Sustainability

Tronix Lighting is affiliated with national recycling systems for electrical and electronic waste. The luminaire is over 90% recyclable when disposed of as electronic waste at end of life. In addition, Tronix Lighting participates in national packaging recycling schemes, ensuring full compliance with both the WEEE and packaging directives.



168-167 Track spot | 48V | linear | black | 8W | 3000K | 100° | DALI

### Laboratory and equipment

Laboratory owner and location	Tronix Lighting BV. Uden. The Netherlands
Gonio spectrometer system and type	Viso Systems Type C. horizontal
Spectrometer manufacturer and model	(Gonio) Ocean Optics STS VIS (Sphere) Admesy HERA VIS 380–780nm
Flicker meter manufacturer and model	Viso Systems LabFlicker
Oscilloscope manufacturer and model	Tektronix MDO3024 oscilloscope (4 Channels. 200 MHz)
Power meter manufacturer and model	Vitretek PA900 Precision Multi-Channel Harmonic Power Analyzer
Power source manufacturer and model	(DC) Keithley Source Measure Unit SMU-2420 3A DC Source Meter (AC) Chroma 61601 AC Source
Datalogger Manufacturer and Model	Omega 8-Channel Thermocouple Thermometer/Data Logger

### Measurement conditions gonio spectrometer

Number of C-planes and Resolution	8 planes – 45°
γ (gamma)-Resolution	1°
Test Distance	1.81 m
Room Temperature and Humidity	22°C +/- 10% – RH 50% +/- 20%
Input Power. Power and Displacement Factors	7.0 W – PF 1.0 – DPF 1.0
Frequency of Input Power	0 Hz
Warm-up Time and Variation	Lamp stabilized in 15 min 2 sec --1.9%

### Tested light source

Manufacturer and Order Code	Tronix Lighting – 168-167
Product Description	Track spot   48V   linear   black   8W   3000K   100°   DALI

### Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	422 lm – 0.81% / 99.19%
Efficiency	60 lm/W
Energy efficiency class	G
Peak Intensity and Beam Angle	168 cd – 101.3°
Correlated Colour Temperature	CCT = 3015 K
Colour Shift. CIE duv	Duv -0.0014
Colour Rendering Index	CRI 95.3
Colour Rendering TM30-18	R <sub>f</sub> 92.7 – R <sub>g</sub> 100.3
Television Lighting Consistency Index	TLCI = 95
Flicker	SVM n/a – PstLM n/a



168-167 Track spot | 48V | linear | black | 8W | 3000K | 100° | DALI

Electrical measurement details

**Input Power**

RMS Input voltage feed. $V_{RMS}$	48.0 V
RMS Input current feed. $I_{RMS}$	0.147 A
Total input power	7.0 W
Frequency of input power	0 Hz
Power factor	1.0
Displacement power factor	1.0
Total harmonic distortion of the current	0%
Total harmonic distortion of the voltage	0%

**Input Power Curve**

Voltage - Current



**Efficiency**

Radiated power efficiency: 21.7%



Lumen efficiency: 60 lm/W



**Current Harmonics %**



**Harmonics**

3rd Harmonic	n/a
5th Harmonic	n/a
7th Harmonic	n/a
9th Harmonic	n/a
11th Harmonic	n/a

Stabilization Details

**Warm-up Conditions**

Stable period	15 min
Stable change max	2.0%
Minimum warm-up time	15 min

**Colour temperature change during warm-up**

CCT start	3022 K
CCT shift	-7 K
CCT end	3015 K

**Warm-up Results**

Total warmup time	Lamp stabilized in 15 min 2 sec
Warmup variation	-1.9%

**Output intensity change during warm-up**

Output start	430 lm
Output change	-8 lm
Output end	422 lm


168-167 Track spot | 48V | linear | black | 8W | 3000K | 100° | DALI

## Colour measurement details



Total lumen output 422 lm  
 Correlated Colour Temperature 3015 K  
 Colour coordinates CIE 1931 (x;y) = (0.434;0.400)  
 Colour deviation from BBL Duv = -0.0014

TM30-18 Colour Fidelity Index  $R_f$  92.7  
 TM30-18 Colour Gamut Index  $R_g$  100.3  
 Colour Rendering Index (Ra) CRI 95.3  
 Colour Rendering Index. (red component)  $R_9 = 73.0$


Colour Quality Scale CQS = 92.4  
 Television Lighting Consistency Index TLCI = 95



Relative spectral power distribution



## TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	$R_f$	Shifts (%)	
		Chroma	Hue
C1	93	-3%	0%
C2	94	-2%	2%
C3	92	-1%	4%
C4	95	-1%	1%
C5	93	-2%	2%
C6	96	2%	0%
C7	94	-2%	0%
C8	98	0%	0%
C9	95	-1%	3%
C10	90	0%	7%
C11	88	2%	8%
C12	90	5%	2%
C13	93	3%	-4%
C14	90	5%	-7%
C15	91	0%	-5%
C16	88	0%	-10%



TM30-18  $R_f$ -values per reference colour




TM30-18  $R_f$ -values per hue bin




TM30 Chroma shift

## Colour Quality details



Colour Rendering Index



Colour Quality Scale



168-167 Track spot | 48V | linear | black | 8W | 3000K | 100° | DALI

Flicker / temporal light artefacts details

**Measurement conditions**

Flicker meter type	Viso Systems LabFlicker
Flicker/TLA sample rate	n/a samples/s
Measurement time	5x 180 seconds (15 minutes) for PstLM. 1.2 sec for all other indices

**Flicker indices according to Illuminating Engineering Society (IES)**

Flicker frequency	n/a Hz
Percent flicker	n/a %
Flicker index	n/a

**TLA indices (according IEC TR 61547-1, EN 61000-3-3 and EN 61000-4-15)**

An LED luminaire is considered flicker-free if the SVM value is  $\leq 0.4$  and if the PstLM value is  $\leq 1.0$

PstLM value ( $F < 80$ Hz)	n/a
SVM value ( $80 < F < 2000$ Hz)	n/a

**Flicker frame (one flicker period in time domain)**



**Flicker FFT (flicker curve in frequency domain)**



**IEEE 1789-2015 Lighting Flicker Risk Zones**



Document revision date: 11-12-2025 Measurement serial: VFR-251209-12563-SW




168-167 Track spot | 48V | linear | black | 8W | 3000K | 100° | DALI

Beam angle

**Luminous Intensity diagram**

Unit: 0-100% of peak intensity




**Main Values**

Output (total Lumen)	422 lm
Lumen Up/Down	0.81% / 99.19%
Peak Intensity	168 cd
Beam Angle (50%)	101.3°
Beam Angle (90%)	101.3°
Beam Angle (10%)	101.3°
<b>Cut-off Angle</b>	
Average 2.5%	169.1°
<b>Field Angle</b>	
Average 10%	155.6°
<b>Intensity Ratio</b>	
In 120° cone	81.2%
In 90° cone	57.0%

**C planes**

- C000-C180
- C090-C270

**Linear distribution diagram - Intensity (candela) vs γ-angle**




Document revision date: 11-12-2025 Measurement serial: VFR-251209-12563-SW



168-167 Track spot | 48V | linear | black | 8W | 3000K | 100° | DALI

Beam Details



\*Measured at center of beam

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
168	42	19	10	7	5	3	3	2	2	1	1	1	1	1	1	1	1	0	0	lux
15.6	3.9	1.7	1	0.6	0.4	0.3	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	0	0	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
168	167	163	158	151	143	133	122	110	98	86	73	60	47	35	23	12	4	1	1	cd
100%	99%	97%	94%	90%	85%	79%	73%	66%	58%	51%	43%	36%	28%	21%	14%	7%	2%	0%	0%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
168	167	163	158	151	143	133	122	110	98	86	73	60	47	35	23	12	4	1	1	cd
100%	99%	97%	94%	90%	85%	79%	73%	66%	58%	51%	43%	36%	28%	21%	14%	7%	2%	0%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
168	167	163	158	151	143	133	122	110	98	86	73	60	47	35	23	12	4	1	1	cd
100%	99%	97%	94%	90%	85%	79%	73%	66%	58%	51%	43%	36%	28%	21%	14%	7%	2%	0%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
168	167	163	158	151	143	133	122	110	98	86	73	60	47	35	23	12	4	1	1	cd
100%	99%	97%	94%	90%	85%	79%	73%	66%	58%	51%	43%	36%	28%	21%	14%	7%	2%	0%	0%	of 0°val

Document revision date: 11-12-2025 Measurement serial: VFR-251209-12563-SW





168-167 Track spot | 48V | linear | black | 8W | 3000K | 100° | DALI

Light Planning – UGR table

Uncorrected, comprehensive UGR table according to CIE 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	23.5	24.7	23.8	25.0	25.2	23.5	24.7	23.8	25.0	25.2
	3H	24.8	26.0	25.2	26.3	26.5	24.8	26.0	25.2	26.3	26.5
	4H	25.3	26.4	25.7	26.7	27.0	25.3	26.4	25.7	26.7	27.0
	6H	25.7	26.7	26.0	27.0	27.3	25.7	26.7	26.0	27.0	27.3
	8H	25.7	26.7	26.1	27.0	27.4	25.7	26.7	26.1	27.0	27.4
	12H	25.7	26.7	26.1	27.0	27.5	25.7	26.7	26.1	27.0	27.5
4H	2H	24.1	25.2	24.5	25.5	25.8	24.1	25.2	24.5	25.5	25.8
	3H	25.6	26.6	26.0	26.9	27.4	25.6	26.6	26.0	26.9	27.4
	4H	26.2	27.0	26.6	27.5	28.0	26.2	27.0	26.6	27.5	28.0
	6H	26.6	27.4	27.1	27.8	28.1	26.6	27.4	27.1	27.8	28.1
	8H	26.7	27.4	27.2	27.8	28.2	26.7	27.4	27.2	27.8	28.2
	12H	26.7	27.3	27.2	27.7	28.2	26.7	27.3	27.2	27.7	28.2
8H	4H	26.4	27.2	26.9	27.5	27.9	26.4	27.2	26.9	27.5	27.9
	6H	26.9	27.5	27.4	28.0	28.5	26.9	27.5	27.4	28.0	28.5
	8H	27.1	27.6	27.6	28.1	28.7	27.1	27.6	27.6	28.1	28.7
	12H	27.1	27.6	27.7	28.1	28.7	27.1	27.6	27.7	28.1	28.7
12H	4H	26.4	27.0	26.9	27.4	27.9	26.4	27.0	26.9	27.4	27.9
	6H	27.0	27.5	27.5	28.0	28.6	27.0	27.5	27.5	28.0	28.6
	8H	27.1	27.5	27.7	28.0	28.7	27.1	27.5	27.7	28.0	28.7

Variations with the observer position for the luminaire spacings. S:

S = 1.0H	0.1 / -0.1	0.1 / -0.1
S = 1.5H	0.2 / -0.4	0.2 / -0.4
S = 2.0H	0.6 / -0.7	0.6 / -0.7

Coefficients of Utilization

Ceiling reflectance	80	70	50	30	10	0												
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	0			
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0			
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	106	106	106	101	101	101	99	
1	109	105	101	97	106	102	99	95	98	95	92	94	91	89	90	88	86	84
2	100	92	85	80	97	90	84	79	86	81	77	83	79	75	80	76	73	71
3	91	81	73	67	89	79	72	66	76	70	65	73	68	64	71	66	62	60
4	84	72	63	57	81	71	63	56	68	61	56	66	60	55	63	58	54	52
5	77	65	56	49	75	63	55	49	61	54	48	59	53	48	57	52	47	45
6	71	58	49	43	69	57	49	43	55	48	43	54	47	42	52	46	42	40
7	66	53	44	38	64	52	44	38	50	43	38	49	42	37	48	42	37	35
8	62	48	40	34	60	48	40	34	46	39	34	45	38	34	44	38	33	32
9	58	44	36	31	56	44	36	31	43	36	31	42	35	30	40	35	30	28
10	54	41	33	28	53	41	33	28	40	33	28	39	32	28	38	32	28	26