

Optix Linear Surface 1200 Direct-Indirect
OPTIX LINEAR SURFACE 1200 D/I 4000K C9 ALU DALI EM
2023818



PRODUCT OVERVIEW

Product name	OPTIX LINEAR SURFACE 1200 D/I 4000K C9 ALU DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	4100
Luminaire efficacy (lm/W)	114
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	85
Total power consumption (W)	36
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238187

DATA TABLE

General data	
Product name	OPTIX LINEAR SURFACE 1200 D/I 4000K C9 ALU DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel

Optix Linear Surface 1200 Direct-Indirect

OPTIX LINEAR SURFACE 1200 D/I 4000K C9 ALU DALI EM

2023818

Mount	Suspended
Fixture rating	Enclosed
Performance ambient temperature Tq (°C)	25
Warranty	5 years

Optical data

Fixture luminous flux (lm)	4100
Luminaire efficacy (lm/W)	114
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	85
Emergency duration (h)	3

Electrical data

Total power consumption (W)	36
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.98
Electrical protection	Class I
Control gear type	LED driver constant current
Drive current (mA)	225
Inrush Current (A)	29
Inrush Duration (µs)	180
Energy Efficiency Class (A->G) of contained light source	D, C(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27
Connectable conductor cross section - Min (mm²)	2.5
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B20	107500
Lifespan L90 B10	48500

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1160

Optix Linear Surface 1200 Direct-Indirect





OPTIX LINEAR SURFACE 1200 D/I 4000K C9 ALU DALI EM
2023818

Nominal Product Width (mm)	90
Weight (kg)	4.25

Packaging

Single packaging type	Carton
Product EAN number	5025768238187
Packaging single width (cm)	10.0
Packaging single depth (cm)	11.0
DUN14 (outer)	05025768238187
Packaging outer length / height (cm)	119.0

PHOTOMETRY



TECHNICAL DRAWINGS

