


Concord

Solstice 150 1250lm 930 SSC01D GB
2070235



Features

- The Solstice 150 1250lm 930 SSC GBis a high efficient SSC GBdimmmable downlight luminaire, Colour rendering index Ra>90, Colour temperature: 3000K Warm White, Class II, Protection rating IP40/IP20, Cut out dimensions: 150mm.

Product Overview


Product name	Solstice 150 1250lm 930 SSC01D GB
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Retail
ETIM Class	EC001744
E-number FI	4262061
Fixture luminous flux (lm)	1250
Luminous flux (lm)	1250
Luminaire efficacy (lm/W)	83
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	70
Glare control	< 19

Concord

Solstice 150 1250lm 930 SSC01D GB
2070235

Photobiological Risk Group	RG0
Total power consumption (W)	15
Electrical protection	Class II
Control gear type	LED driver constant current
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9005
IP rating	IP40/20
IK rating	IK02
Product EAN number	5025768702350
Warranty	5 years
Dimming method	SylSmart SSC
Useful luminous flux (#use)	1250

Photometry



Technical drawings

