

# Concord

## Raiden IP66 40KLM 830 Asymmetric Wide 2824022



### Features

- Outdoor and indoor floodlight range with in house design, comes complete with 1m flying lead and adjustable bracket, aluminium housing, RAL 9022 - Pearl light grey, clear glass diffuser, IP66, IK08, Class I, 3000K, Non-dimming, 38700lm, 294W, 132lm/W, CRI80, Asymmetric Wide beam angle 110\*50°, 100000 hrs L90B50 lifespan, 561x569x76mm (LxWxH) dimensions, 13.4kg weight. Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3 only with the separate wire guard accessory fitted.

### Product Overview

Product name	Raiden IP66 40KLM 830 Asymmetric Wide
Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Logistics & Industry
ETIM Class	EC001744
Fixture luminous flux (lm)	38700
Luminaire efficacy (lm/W)	132
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	110*50
Photobiological Risk Group	RG2
Total power consumption (W)	294
Electrical protection	Class I
Housing colour	RAL9022
IP rating	IP66
IK rating	IK08
Product EAN number	5025768240227

# Concord

## Raiden IP66 40KLM 830 Asymmetric Wide 2824022


Warranty

5 years

Dimming method

N/A

### Photometry



### Technical drawings

