

OPTIX RECESSED 600 2L LUMI 4K ALU DALI 2023833



Features

• OPTIX RECESSED 600 2L LUMI 4000K ALU DALI is a ceiling recessed luminaire for office and education applications with Aluminised plastic extra low glare optics and RAL9016 colour fixture body. DALI dimmable. 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. For 4000K - Colour rendering index Ra >98; Melanopic Ratio MEER: 0.771; Fidelity Index R#: 94; Gamut Index R#: 98. For 4000K luminous flux: 2900lm. Power consumption: 30W. Luminaire efficacy: 97lm/W. UGR<16 Luminance at 65°<200 Cd/m2, IK07, IP20. Photobiological safety risk group 0. Electrical protection Class I. Glow wire test 850°C. 60,000hrs L80B20 lifespan.


Product Overview

Product name	OPTIX RECESSED 600 2L LUMI 4K ALU DALI
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Fixture luminous flux (lm)	2915
Luminaire efficacy (lm/W)	97
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	98
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	30
Electrical protection	Class I


OPTIX RECESSED 600 2L LUMI 4K ALU DALI
2023833

Control gear type	LED driver constant current
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238330
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	OPTIX RECESSED 600 2L LUMI 4K ALU DALI
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2915
Luminaire efficacy (lm/W)	97
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	98
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	30
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.98
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	200
Inrush Current (A)	29

OPTIX RECESSED 600 2L LUMI 4K ALU DALI 2023833

Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	60000

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	596
Nominal Product Width (mm)	596
Weight (kg)	5.0

PACKAGING

Single packaging type	Carton
Product EAN number	5025768238330
Packaging single width (cm)	6.5
Packaging single depth (cm)	65.0
DUN14 (outer)	05025768238330
Packaging outer length / height (cm)	62.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No

Concord

OPTIX RECESSED 600 2L LUMI 4K ALU DALI
2023833

Suitable for household illumination

No