


VKEK-V-1PO-RED: Synthetic Manifold 1X Po Euroconus - Red



Commercial information

With the Henco Pro-Flow Manifold, you benefit from the following features:

- Multifunctional, self-aligning design and modularity: 2 circuits, upward and downward.
- A dedicated pipe circuit for each draw-off point; connections in the floor can therefore be avoided.
- 100% corrosion-free.
- A change in the dew point results in a lower risk of condensation in cold water systems.
- Maximum number of connections in a very short installation length.
- Improves system balance.
- Closing off a single circuit is possible, simplifying maintenance.
- Suitable for both press-fit and push-fit applications.
- Supply in 20 mm and 26 mm - Henco thread dimensions female thread x male thread.
- Certified for drinking water.
- Various group connections available in 3/4" Eurocone:
 - Synthetic compression fitting
 - Synthetic press fitting
 - Brass press fitting
 - Synthetic push-fit fitting
- Not compatible with metal (Eurocone) compression fittings.
- Available with 4 different handle colours, making it easy to identify different applications.

Basic unit dimensions

Height	89 mm
Length	69 mm
Width	52 mm
Net weight	0.085 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Suitable for tap water	✓	Number of branches	2
Suitable for central heating water	✓	Number of branching directions	2
Suitable for cooling water	✓	Distance between offset	40 Millimetre
Suitable for compressed air	✗	Max. medium temperature (continuous)	95 Degrees celsius
Suitable for glycol	✓	Width	68.74 Millimetre
Suitable for ethanol	✗	Height	88.5 Millimetre
Suitable for gas	✗	Depth	52.23 Millimetre
Mounting method	Surface mounting	Length distributor	68.74 Millimetre
Model	Distributor/collector		
Material	Plastic		
Material quality	Polyphenylsulfone (PPSU)		
Surface protection	Untreated		
Shape	Throughflow with straight branches		
System specific	✓		
With fill- and drain valve	✗		
With backflow safeguard	✗		
With shut-off valve	✓		
With de-aeration	✗		
With wall-mounting bracket	✗		
With mounting material	✗		
With legs	✗		
With adjustable floor legs	✗		
With insulation	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		