

Optix Recessed 600x600 Standard Output
OPTIX RECESSED 600 2L LUMI 4K ALU SSC
2023834




PRODUCT OVERVIEW

Product name	OPTIX RECESSED 600 2L LUMI 4K ALU SSC
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	2915
Luminaire efficacy (lm/W)	94
Light colour	Neutral White
CRI (Ra)	98
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	31
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238347

PHOTOMETRY

Optix Recessed 600x600 Standard Output
OPTIX RECESSED 600 2L LUMI 4K ALU SSC
2023834



Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	0.75	37.9°	1222
0.5	0.75	38.0°	1517
0.5	0.75	38.1°	1633
1.0	1.56	37.9°	1830
1.0	1.56	38.0°	454
1.0	1.56	38.1°	481
1.5	2.34	37.9°	814
1.5	2.34	38.0°	222
1.5	2.34	38.1°	235
2.0	3.11	37.9°	488
2.0	3.11	38.0°	114
2.0	3.11	38.1°	119
2.5	3.88	37.9°	290
2.5	3.88	38.0°	73
2.5	3.88	38.1°	77
3.0	4.67	37.9°	203
3.0	4.67	38.0°	50
3.0	4.67	38.1°	53

TECHNICAL DRAWINGS

