



15-FLEX32: Hencoflex 2x Ø32x3 15m



Commercial information

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Demi Water, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material inner layer	Plastic	Commercial length	15 Metre
Material intermediate layer	Aluminium	Outer pipe diameter	32 Millimetre
Material outer layer	Plastic	Wall thickness	3 Millimetre
Glass-fibre reinforced		Medium temperature (continuous)	- Degrees celsius 10 9 5
	✘		
Diffusion-proof	✓	Max. medium temperature (momentarily)	95 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	16 Bar
Jacket colour	Black	Wall roughness	0.00 Millimetre 7
Flexible	✘	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Suitable for surface mounting	✓	Min. bending radius	0 Millimetre
Pipe colour	Black	Min. bending radius without tools	0 Millimetre
With mantle pipe	✓	Outer diameter mantle pipe	125 Millimetre
With heating cable	✘	Lambda value	0.29 Watt per meter Kelvin 3
Colour outer sheath	Black	Outer diameter thermal insulation	0 Millimetre
With thermal insulation	✓	Outer width rectangular insulation	0 Millimetre
Shape of insulation	Round	Outer height rectangular insulation	0 Millimetre
Colour of thermal insulation	Grey		
Capped	✘		
UV resistant	✓		
Type approval according to BBR/EKS	✘		

Related products