



Features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 8500lm; 61W; 139lm/W; 6500K; SDCM<5; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark.


Product Overview

Product name	Resisto 1500 IP66 8500lm 865
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
E-number FI	4357061
Fixture luminous flux (lm)	8500
Luminaire efficacy (lm/W)	139
Colour temperature (K)	6500
CRI (Ra)	80
Colour Consistency (SDCM)	5
Colour Variation Initial (SDCM)	5
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	61
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey


Resisto 1500 IP66 8500lm 865
0010248

IP rating	IP66
IK rating	IK08
Product EAN number	5410288102481
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	Resisto 1500 IP66 8500lm 865
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
E-number FI	4357061
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	8500
Luminaire efficacy (lm/W)	139
Colour temperature (K)	6500
CRI (Ra)	80
Colour Consistency (SDCM)	5
Colour Variation Initial (SDCM)	5
Glare control	< 25
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	61
Primary Supply/Product voltage - min (V)	220
Lamp power factor	1
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	350



Resisto 1500 IP66 8500lm 865
0010248

Inrush Current (A)	16
Inrush Duration (µs)	40
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	24
Max. products per 20A B Breaker	49
Connectable conductor cross section - Max (mm²)	2.5

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	69000
Lifespan L90 B10	31000

PHYSICAL DATA

Housing colour	Grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1500
Nominal Product Width (mm)	87
Weight (kg)	1.95

PACKAGING

Single packaging type	Carton
Product EAN number	5410288102481
Packaging single width (cm)	10.0
Packaging single depth (cm)	8.5
DUN14 (outer)	05410288102481
Packaging outer length / height (cm)	150.5

SAFETY DATA



Resisto 1500 IP66 8500lm 865
0010248

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No