


Optix Recessed 600x600 Medium Output  
*OPTIX RECESSED 600 3L LUMI 4K ALU*  
2023842



PRODUCT OVERVIEW

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Product name                    | OPTIX RECESSED 600 3L LUMI 4K ALU |
| Technology                      | LED LumiNature                    |
| Cap/Base                        | N/A                               |
| Housing                         | Steel                             |
| Mount                           | Ceiling recessed mounting         |
| Fixture rating                  | Enclosed                          |
| Warranty                        | 5 years                           |
| Fixture luminous flux (lm)      | 3750                              |
| Luminaire efficacy (lm/W)       | 102                               |
| Light colour                    | Neutral White                     |
| CRI (Ra)                        | 98                                |
| Colour Variation Initial (SDCM) | SDCM3                             |
| Colour Consistency (SDCM)       | 3                                 |
| Glare control                   | < 16                              |
| Photobiological Risk Group      | RG1                               |
| Total power consumption (W)     | 37                                |
| Electrical protection           | Class I                           |
| Control gear type               | LED driver constant current       |
| Housing colour                  | RAL 9016 - Traffic white / Bezel  |
| IP rating                       | IP20                              |
| IK rating                       | IK07                              |
| Product EAN number              | 5025768238422                     |

DATA TABLE

|                |                                   |
|----------------|-----------------------------------|
| General data   |                                   |
| Product name   | OPTIX RECESSED 600 3L LUMI 4K ALU |
| Technology     | LED LumiNature                    |
| Cap/Base       | N/A                               |
| Housing        | Steel                             |
| Mount          | Ceiling recessed mounting         |
| Fixture rating | Enclosed                          |

## Optix Recessed 600x600 Medium Output

### OPTIX RECESSED 600 3L LUMI 4K ALU

### 2023842

|                                         |              |
|-----------------------------------------|--------------|
| Operating temperature range (°C)        | 10°C...+25°C |
| Performance ambient temperature Tq (°C) | 25           |
| Warranty                                | 5 years      |

#### Optical data

|                                         |               |
|-----------------------------------------|---------------|
| Fixture luminous flux (lm)              | 3750          |
| Luminaire efficacy (lm/W)               | 102           |
| Correlated colour temperature range (K) | 2800 - 6200   |
| Light colour                            | Neutral White |
| CRI (Ra)                                | 98            |
| Colour Variation Initial (SDCM)         | SDCM3         |
| Colour Consistency (SDCM)               | 3             |
| Glare control                           | < 16          |
| Photobiological Risk Group              | RG1           |

#### Electrical data

|                                                          |                             |
|----------------------------------------------------------|-----------------------------|
| Total power consumption (W)                              | 37                          |
| Primary Supply/Product voltage - min (V)                 | 198.0                       |
| Lamp power factor                                        | 0.95                        |
| Electrical protection                                    | Class I                     |
| Control gear type                                        | LED driver constant current |
| Drive current (mA)                                       | 250                         |
| Glow Wire Test (°C)                                      | 850                         |
| Energy Efficiency Class (A->G) of contained light source | F                           |
| Nominal Frequency (Hz)                                   | 50/60Hz                     |
| Max. products per 10A C Breaker                          | 27                          |
| Max. products per 20A B Breaker                          | 35                          |
| Connectable conductor cross section - Max (mm²)          | 2.5                         |

#### Lifetime data

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B20 | 60000  |

#### Physical data

|                             |                                  |
|-----------------------------|----------------------------------|
| Housing colour              | RAL 9016 - Traffic white / Bezel |
| IP rating                   | IP20                             |
| IK rating                   | IK07                             |
| Diffuser finish             | Matt/satinized                   |
| Diffuser material           | PC Polycarbonate                 |
| Nominal Product Length (mm) | 596                              |
| Nominal Product Width (mm)  | 596                              |
| Weight (kg)                 | 5.0                              |

#### Packaging

|                             |               |
|-----------------------------|---------------|
| Single packaging type       | Carton        |
| Product EAN number          | 5025768238422 |
| Packaging single width (cm) | 6.5           |

## Optix Recessed 600x600 Medium Output

### OPTIX RECESSED 600 3L LUMI 4K ALU



### 2023842

|                                      |                |
|--------------------------------------|----------------|
| Packaging single depth (cm)          | 65.0           |
| DUN14 (outer)                        | 05025768238422 |
| Packaging outer length / height (cm) | 62.0           |

#### Safety data

|                                  |       |
|----------------------------------|-------|
| Optimal operating condition (°C) | 10-25 |
|----------------------------------|-------|

## PHOTOMETRY



## TECHNICAL DRAWINGS

