

Product data


Product code	VC05-0243	STK-code	1914280	EAN-code	6410019142808
Product name	OTL PEN-connector 2xAl/Cu 1,5-50mm ² (Ye/Gr/Blue)			ETIM class	EC000897
Wires	2xAl/Cu 1,5-50 mm ²				

Technical data

Nominal current (IEC)	Cu	320	A
	Al	290	A
Nominal voltage (IEC)	1000 V AC / 1500 V DC		
		-	
		-	
		-	
Number of poles		1	pcs
Max. Cross section		50	mm²
Tightening torque			
	1,5-2,5 mm²	1,5	Nm
	4-10 mm²	5	Nm
	16-50 mm²	10	Nm
		-	
Min. installation temperature		+5	°C
Operating temperature		-25...+80	°C
Weight		90	g
IP-protection		IP20	
	-		
Color / Material	Grey Housing RAL 7035/PA66-V0		
Mounting / Connection	DIN-rail mounting		


Description

OTL-connectors are designed for connecting and branching aluminium and copper conductors. The body is made of tin plated aluminium. Housing is made of UL94 V0 class polyamide. Made in Finland.

Drawing

Package

Package	Box	Pcs / Package	54	Weight [kg]	5,00
Length [mm]	285	Width [mm]	180	Height [mm]	115

Ouneva Oy

Teollisuustie 21
FI-82730 Tuupovaara
Finland

www.ounevagroup.fi
www.ounevaproducts.fi