

Optix Recessed 600x600 Medium Output
OPTIX RECESSED 600 3L LUMI HCL TW ALU DALI
2023845




PRODUCT OVERVIEW

Product name	OPTIX RECESSED 600 3L LUMI HCL TW ALU DALI
Technology	LED Luminaire
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	3510
Luminaire efficacy (lm/W)	95
Light colour	Tuneable White HCL
CRI (Ra)	96
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	37
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238453

PHOTOMETRY

Optix Recessed 600x600 Medium Output
OPTIX RECESSED 600 3L LUMI HCL TW ALU DALI
2023845



Distance (m)	Cone diameter (m)	Beam angle (°)	Illuminance (lx)
0.5	0.75	76.9°	2748
1.0	1.50	76.9°	687
1.5	2.25	76.9°	304
2.0	3.00	76.9°	227
2.5	3.75	76.9°	180
3.0	4.50	76.9°	156

TECHNICAL DRAWINGS

