


Optix Recessed 600x600 Medium Output
OPTIX RECESSED 600 3L LUMI HCL TW ALU SSC
2023846



PRODUCT OVERVIEW

Product name	OPTIX RECESSED 600 3L LUMI HCL TW ALU SSC
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	3510
Luminaire efficacy (lm/W)	93
Light colour	Tuneable White HCL
CRI (Ra)	96
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	38
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238460

DATA TABLE

General data	
Product name	OPTIX RECESSED 600 3L LUMI HCL TW ALU SSC
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed

Optix Recessed 600x600 Medium Output

OPTIX RECESSED 600 3L LUMI HCL TW ALU SSC

2023846

Operating temperature range (°C)	10°C...+25°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

Optical data

Fixture luminous flux (lm)	3510
Luminaire efficacy (lm/W)	93
Correlated colour temperature range (K)	2800 - 6200
Light colour	Tuneable White HCL
CRI (Ra)	96
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	38
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.95
Electrical protection	Class I
Control gear type	LED driver constant current
Drive current (mA)	165
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	13
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	68000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	596
Nominal Product Width (mm)	596
Weight (kg)	5.0


Packaging

Single packaging type	Carton
Product EAN number	5025768238460
Packaging single width (cm)	6.5
Packaging single depth (cm)	65.0

Optix Recessed 600x600 Medium Output
OPTIX RECESSED 600 3L LUMI HCL TW ALU SSC
2023846

DUN14 (outer)	05025768238460
Packaging outer length / height (cm)	62.0
Safety data	
Optimal operating condition (°C)	10-25

PHOTOMETRY



TECHNICAL DRAWINGS

