

Product data sheet

Item No. 96.051.6053.0

Female connector RST20I5S B1 M00 GL

Device connectors, modular M20, RST20i5, 5 pole, straight, female, screw connection, 250/400V, 20A, color of coding: light gray, color of housing: light gray



Item No.	96.051.6053.0
EAN	4015573862005
Order Unit	100 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	20 A
Rated voltage	400 V
Pollution degree	3
Mechanical coding	Yes
Rated impulse voltage	4 kV
Interlockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	
Color of separate adapter (if present)	Light grey

Connection Data

Connection cross section solid	4 mm ²
Connection cross section stranded	4 mm ²
Terminations per pole	1

Model

Model	female
Number of poles	5



Connection type	Screw connection
Connecting thread metric	M20
Angle of plug	Straight
Degree of protection (IP)	IP66/IP68
Built-in component	Snap-in/screw-in

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	68.2 mm
Width	35 mm
Height	35 mm

Technical drawing

Auslieferungszustand / delivery status

Verpackungseinheit: je 100 Stück / packaging unit: per 100

M1:1

Teile-Nr. / part-nr.	Farbe: / color:	Type
96.051.6053.1	schwarz, ähnl. RAL 9005 / black, similar to RAL 9005	RST2015S B1 M00V SW
96.051.6053.0	lichtgrau, ähnl. RAL 7035 / lightgrey, similar to RAL 7035	RST2015S B1 M00V GL

12.09.2011/	1:1	1	1	1	1
26.07.2011/					
27.01.2011/					
02.12.2006/					

wieland
Mischreihe Verbindungen

BUCHSENADAPTER M20
female connector adapter M20
mit Schraubanschluß ohne Drahtschleifstrom-connection without wire protection
Stromschleifstrom Schutzring Serie 9 125000000000

1. Verwendung: -
Erst- / first placement for: -
Type: Buchsenadapter M20

Zeichnung Nr. / drawing No.: 96.051.6053.0 01K d
Made in mm / dimensions are in mm