



### Features

- QUADRO 1200X300 840 SSA03 Unique stylish recessed modular LED luminaire, ideal for general indoor lighting applications such as breakout areas, offices and meeting rooms. Steel frame with integrated reflector, passive cooling. Low glaring UGR<16. RG1, 75° beam angle, optical system: white painted reflector with total internal reflection lenses. Light color temperature: 4000K (Neutral White), total system power: 35W, total fixture output: 4650lm, efficacy at max output to 133 lm/W, CRI (Ra) >80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), lifespan: 88,000 hours at 80% of the original output (L80B20), IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, low flicker, Sylsmart Connected enabled, electrical protection: Class II. Ingress protection IP40/IP20, suitable for indoor environment only. Nominal size: 1195x295mm, Loop in / loop out wiring, safety cables included, 18mm nominal height, RAL 9003 - Signal white color frame, weight: 3,60kg.

### Product Overview

|                            |                           |
|----------------------------|---------------------------|
| Product name               | QUADRO 1200x300 840 SSA03 |
| Technology                 | LED (3 SDCM)              |
| Cap/Base                   | N/A                       |
| Housing                    | Steel                     |
| Mount                      | Ceiling recessed mounting |
| General application        | Education, Office         |
| ETIM Class                 | EC002892                  |
| E-number FI                | 4170584                   |
| Fixture luminous flux (lm) | 4650                      |
| Luminaire efficacy (lm/W)  | 133                       |

