


Optix Linear Surface 1200 Direct
OPTIX LINEAR SURFACE 1200 LUMI 4K ALU DALI
2023853



PRODUCT OVERVIEW

Product name	OPTIX LINEAR SURFACE 1200 LUMI 4K ALU DALI
Technology	LED Luminaire
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	2870
Luminaire efficacy (lm/W)	96
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	98
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	30
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238538

DATA TABLE

General data	
Product name	OPTIX LINEAR SURFACE 1200 LUMI 4K ALU DALI
Technology	LED Luminaire
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting

Optix Linear Surface 1200 Direct

OPTIX LINEAR SURFACE 1200 LUMI 4K ALU DALI

2023853

Fixture rating	Enclosed
Performance ambient temperature Tq (°C)	25
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2870
Luminaire efficacy (lm/W)	96
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	98
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	30
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.98
Electrical protection	Class I
Control gear type	LED driver constant current
Drive current (mA)	200
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	60000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1129
Nominal Product Width (mm)	90
Weight (kg)	3.25

Packaging

Single packaging type	Carton
Product EAN number	5025768238538

Optix Linear Surface 1200 Direct


OPTIX LINEAR SURFACE 1200 LUMI 4K ALU DALI
2023853

Packaging single width (cm)	10.0
Packaging single depth (cm)	11.0
DUN14 (outer)	05025768238538
Packaging outer length / height (cm)	119.0

PHOTOMETRY

0.5	0.77	E(0°) E(C0)	37.7°	7289 1810
1.0	1.55	E(0°) E(C0)	37.7°	1522 453
1.5	2.32	E(0°) E(C0)	37.7°	910 201
2.0	3.09	E(0°) E(C0)	37.7°	456 112
2.5	3.86	E(0°) E(C0)	37.7°	292 72
3.0	4.64	E(0°) E(C0)	37.7°	202 50

Distance [m] Cone diameter [m] Illuminance [lx]
— C0 - C180 (Half beam angle: 75.4°)



TECHNICAL DRAWINGS

