

Resisto DALI

Resisto 1500 IP66 DALI 4200lm 840
0010259

Product features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 4200lm; 30W; 140lm/W; 4000K; SDCM<5; DALI dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark.




PRODUCT OVERVIEW

| | |
|---------------------------------|---|
| Product name | Resisto 1500 IP66 DALI 4200lm 840 |
| Technology | LED |
| Cap/Base | N/A |
| Housing | PC Polycarbonate |
| Mount | Ceiling surface mounting, Suspended, Wall surface mounted |
| General application | Logistics & Industry |
| ETIM Class | EC002892 |
| E-number FI | 4357067 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | 4200 |
| Luminaire efficacy (lm/W) | 140 |
| Colour temperature (K) | 4000 |
| CRI (Ra) | 80 |
| Colour Consistency (SDCM) | 5 |
| Colour Variation Initial (SDCM) | SDCM5 |
| Beam Angle (°) | 110 |
| Glare control | < 23 |
| Photobiological Risk Group | RG1 |
| Light source included | Fixture without Lightsource |
| Total power consumption (W) | 30 |
| Electrical protection | Class I |
| Control gear type | LED driver constant current |
| Dimmable | Yes |
| Dimming method | DALI |
| Minimum dimming level (%) | 1 |
| LED Flickering Rate | Ultra low (5% or less) |
| Housing colour | Grey |
| IP rating | IP66 |
| IK rating | IK08 |
| Product EAN number | 5410288102597 |

PHOTOMETRY

Resisto DALI

Resisto 1500 IP66 DALI 4200lm 840
0010259



TECHNICAL DRAWINGS

