


UFH-0605MDK07-PRM-BV: 7-groups man. comp,flow meter 0-3L,therm.,washer and air vent 7x + 2 b



Commercial information

Preassembled composite manifold for both residential and non-residential construction. The compact structure of this manifold and its adjustable brackets allow for easy installation. This manifold comes with flow meters and a calibration system per group, as well as with a fill and drain valve and manual vent. The outlet connections are 3/4" eurocone.

These plastic manifolds offer the following advantages:

- Preassembled: simply mount and connect
- Suitable for heating and cooling
- Compact structure
- Suitable for PN6 installations
- Cooling without condensation
- Ball valves UFH-BM0606-VN are included

Basic unit dimensions

Height	335 mm
Length	468 mm
Width	99 mm
Net weight	3.369 kg

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Building installations, Underfloor heating, Industry, Utility

Technical characteristics

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✓	Medium temperature (continuous)	0 60 Degrees celsius
Material	Plastic	Max. operating pressure	6 Bar
Position primary connection	Left/right	Max. number of expansion groups	15
Primary connection	Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1)	Number of groups secondary	7
Nominal diameter primary connection	1 inch (25)	Outer pipe diameter secondary	12 20 Millimetre
With valves on primary connection	✗	Flow-through capacity	0 5 Litre per hour
With mixing valve	✗	Min. pressure difference secondary flow/return	0 Kilo Pascal
Expandable	✓	Width	99 Millimetre
Multi-zone manifold	✗	Height	335 Millimetre
With temperature limit	✗	Depth	468 Millimetre
With non-return valve	✗		
With circulation pump	✗		
Article compression class	PN 6		
With controller	✗		
Hydraulic balance control	None		
Volume flow measurement	Analogue		
With thermometer	✓		
Temperature measurement supply	Analogue		
Temperature measurement return	Analogue		
With de-aeration	✓		
With pressure gauge	✗		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✓		
With flow-through indicator	✓		
With thermal actuator	✗		
With wall-mounting bracket	✓		
With casing	✗		