



Features

• Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 4200lm; 34W; 124lm/W; 4000K; SDCM<5; CRI80; IP65; IK08 (sensor IK03); Class I; 69,000hrs (L80B20) lifespan; 1588mm x 87mm x 80mm; D-mark; SylSmart Standalone enabled, with batten mount PIR sensor.


Product Overview

Product name	Resisto 1500 IP65 4200lm 840 SSC S
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
Fixture luminous flux (lm)	4200
Luminaire efficacy (lm/W)	124
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	5
Colour Variation Initial (SDCM)	5
Glare control	< 23
Photobiological Risk Group	RG1
Total power consumption (W)	34
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)


Resisto 1500 IP65 4200lm 840 SSC S
0010264

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288102641
Warranty	5 years

Photometry



Technical drawings



Resisto 1500 IP65 4200lm 840 SSC S
0010264

Data table

GENERAL DATA

Product name	Resisto 1500 IP65 4200lm 840 SSC S
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
Operating temperature range (°C)	-20°C...+30°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	4200
Luminaire efficacy (lm/W)	124
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	5
Colour Variation Initial (SDCM)	5
Glare control	< 23
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	34
Primary Supply/Product voltage - min (V)	220
Lamp power factor	1
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	350
Inrush Current (A)	29

Resisto 1500 IP65 4200lm 840 SSC S 0010264

Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27
Connectable conductor cross section - Max (mm²)	2.5

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	69000
Lifespan L90 B10	31000

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK08
IK rating of sensor	IK03
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1588
Nominal Product Width (mm)	87
Weight (kg)	2.13

PACKAGING

Single packaging type	Carton
Product EAN number	5410288102641
Packaging single width (cm)	10.0
Packaging single depth (cm)	8.5
DUN14 (outer)	05410288102641
Packaging outer length / height (cm)	150.5



Resisto 1500 IP65 4200lm 840 SSC S
0010264

SAFETY DATA

Optimal operating condition (°C)	-20-30
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No