


Concord

OFFICELYTE 1200 3000K HE SSA03
2069548



Features

• Concord OFFICELYTE 1200 3000K HE SSA03 is a high performance low glare luminaire for offices and education applications. Suitable for lay in, as well as for pull up, into concealed grid and plasterboard ceilings with our optional wedge accessory kits suitable. Optical solution is a combination of Tp(a) rated central prismatic and side diffusers. Painted steel housing with RAL 9016 finishing colour. 1196x296x60mm dimensions. 3300lm luminous flux, 28.5W total power consumption, 116lm/W efficacy level, CRI80 3000K (Warm white) LED light sources with chromaticity tolerance of 3-step MacAdam ellipse. Conforming to EN 12464-1 for indoor work places, UGR<19. IK03 impact resistance, IP20 ingress protection level. IEC Class II electrical protection. Photobiological Risk Group 1. Lifespan 93k hours at L80B50. Glow Wire test 650°C. SylSmart Connected enabled with integrated sensor.

Product Overview


Product name	OFFICELYTE 1200 3000K HE SSA03
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Office, Education
ETIM Class	EC002892
Fixture luminous flux (lm)	3, 300
Luminaire efficacy (lm/W)	116
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80

Concord

OFFICELYTE 1200 3000K HE SSA03 2069548

Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	28.5
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	RAL9016
IP rating	IP20
IK rating	IK03
Product EAN number	5025768695485
Warranty	5 years
Dimming method	SylSmart SSA


Photometry



Concord

OFFICELYTE 1200 3000K HE SSA03
2069548

Technical drawings



Data table

GENERAL DATA

Product name	OFFICELYTE 1200 3000K HE SSA03
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Office, Education
Operating temperature range (°C)	5°C...+35°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3, 300
Luminaire efficacy (lm/W)	116
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Luminous Intensity (cd)	1740
Beam Angle (°)	80

Concord

OFFICELYTE 1200 3000K HE SSA03 2069548

Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	28.5
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) \leq xx.x %	10
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart SSA
Drive current (mA)	750
Inrush Current (A)	15
Inrush Duration (μ s)	220
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	18
Max. products per 16A C Breaker	28
Max. products per 16A B Breaker	18
Connectable conductor cross section - Max (mm ²)	2.5

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B50	93000
Lifespan L90 B50	45000

PHYSICAL DATA

Concord

OFFICELYTE 1200 3000K HE SSA03 2069548

Housing colour	RAL9016
IP rating	IP20
IK rating	IK03
Diffuser finish	Prismatic
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1196
Nominal Product Width (mm)	296
Nominal Product Height (mm)	60
Weight (kg)	5.0

PACKAGING

Product EAN number	5025768695485
Packaging single length / height (cm)	154.0
Packaging single width (cm)	34.0
Packaging single depth (cm)	7.2
DUN14 (inner)	05025768695485
Units per outer package	1
Packaging outer length / height (cm)	154.0
Packaging outer width (cm)	34.0
Packaging outer depth (cm)	7.2

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	5-35
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No