

Resisto HE
Resisto 1500 HE IP66 DALI 9700lm 840
0010275



Product features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 9700lm; 60W; 162lm/W; 4000K; SDCM<3; DALI dimmable; CRi80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark.



PRODUCT OVERVIEW

Product name	Resisto 1500 HE IP66 DALI 9700lm 840
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4357071
Warranty	5 years
Fixture luminous flux (lm)	9700
Luminaire efficacy (lm/W)	162
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	110
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	60
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288102757

DATA TABLE

General data	
Product name	Resisto 1500 HE IP66 DALI 9700lm 840

Resisto HE

Resisto 1500 HE IP66 DALI 9700lm 840

0010275

Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4357071
Warranty	5 years

Optical data

Fixture luminous flux (lm)	9700
Luminaire efficacy (lm/W)	162
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	110
Distribution type	Diffuse
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	60
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	1
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	9
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
No. Of switching cycles before premature failures	>50000
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
Drive current (mA)	350
Inrush Current (A)	23
Inrush Duration (µs)	174
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 13A C Breaker	28
Max. products per 16A C Breaker	35

Resisto HE

Resisto 1500 HE IP66 DALI 9700lm 840

0010275

Max. products per 20A C Breaker	45
Max. products per 10A B Breaker	13
Max. products per 13A B Breaker	17
Max. products per 16A B Breaker	21
Max. products per 20A B Breaker	27
Connectable conductor cross section - Max (mm ²)	2.5

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	69000
Lifespan L90 B10	31000

Physical data

Housing colour	Grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1500
Nominal Product Width (mm)	87
Nominal Product Height (mm)	80
Weight (kg)	2.01

Packaging

Single packaging type	Carton
Product EAN number	5410288102757
Packaging single length / height (cm)	150.5
Packaging single width (cm)	10.0
Packaging single depth (cm)	8.5
DUN14 (outer)	05410288102757
Units per outer package	1
Packaging outer length / height (cm)	150.5
Packaging outer width (cm)	10.0
Packaging outer depth (cm)	8.5

Safety data


Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY

Resisto HE

Resisto 1500 HE IP66 DALI 9700lm 840

0010275



Distance [m]	Cone diameter [m]	C0 - C180 (Half beam angle: 102.9°) C90 - C270 (Half beam angle: 108.4°)	Illuminance [lx]
0.5	1.39	E(0°) E(C90) E(C0)	12908 1296 1574
	1.25	E(0°) E(C90) E(C0)	542° 542° 51.4°
1.0	2.77	E(0°) E(C90) E(C0)	3234 324 394
	2.51	E(0°) E(C90) E(C0)	542° 542° 51.4°
1.5	4.16	E(0°) E(C90) E(C0)	1435 144 175
	3.76	E(0°) E(C90) E(C0)	542° 542° 51.4°
2.0	5.55	E(0°) E(C90) E(C0)	809 81 98
	5.01	E(0°) E(C90) E(C0)	542° 542° 51.4°
2.5	6.93	E(0°) E(C90) E(C0)	515 52 63
	6.26	E(0°) E(C90) E(C0)	542° 542° 51.4°
3.0	8.32	E(0°) E(C90) E(C0)	359 36 44
	7.52	E(0°) E(C90) E(C0)	542° 542° 51.4°

TECHNICAL DRAWINGS

