

Features

• Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 7100lm; 47W; 151lm/W; 4000K; SDCM<5; CRI80; IP66; IK08 (sensor IK03); Class I; 69,000hrs (L80B20) lifespan; 1593mm x 87mm x 80mm; D-mark; SylSmart Connected Industry enabled.


Product Overview

Product name	Resisto 1500 HE IP65 7100lm 840 SSE
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
Fixture luminous flux (lm)	7100
Luminaire efficacy (lm/W)	151
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	47
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey

Resisto 1500 HE IP65 7100lm 840 SSE
0010277

IP rating	IP65
IK rating	IK08
Product EAN number	5410288102771
Warranty	5 years

Photometry



Technical drawings

