



Features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 8300lm; 54W; 154lm/W; 4000K; SDCM<3; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark.


Product Overview

Product name	Resisto 1500 HE IP66 8300lm 840
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
E-number FI	4357139
Fixture luminous flux (lm)	8300
Luminaire efficacy (lm/W)	154
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	54
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey

**Resisto 1500 HE IP66 8300lm 840
0010278**

IP rating	IP66
IK rating	IK08
Product EAN number	5410288102788
Warranty	5 years

Photometry



Technical drawings

