



**Data Sheet | Item Number: 261-161/331-000**  
2-conductor terminal strip; on one side with push-buttons; with snap-in mounting feet; 11-pole; for plate thickness 0.6 - 1.2 mm; Fixing hole 3.5 mm Ø; 2.5 mm²; CAGE CLAMP®; 2,50 mm²; gray  
<https://www.wago.com/261-161/331-000>



Color: ■ gray                      Similar to illustration



Dimensions in mm

**Electrical data**

| Ratings per IEC/EN            |                                                           |
|-------------------------------|-----------------------------------------------------------|
| Nominal voltage (III/3)       | 500 V                                                     |
| Rated impulse voltage (III/3) | 6 kV                                                      |
| Rated current                 | 24 A                                                      |
| Legend (ratings)              | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |

| Approvals per |  | UL 1059 |       |       |
|---------------|--|---------|-------|-------|
| Use group     |  | B       | C     | D     |
| Rated voltage |  | 300 V   | 300 V | 600 V |
| Rated current |  | 15 A    | 15 A  | 5 A   |

| Approvals per |  | CSA 22.2 No 158 |       |       |
|---------------|--|-----------------|-------|-------|
| Use group     |  | B               | C     | D     |
| Rated voltage |  | -               | 300 V | 600 V |
| Rated current |  | -               | 10 A  | 5 A   |

**Connection data**

|                            |    |
|----------------------------|----|
| Connection points          | 22 |
| Total number of potentials | 11 |
| Number of levels           | 1  |

| Connection 1                    |                                   |
|---------------------------------|-----------------------------------|
| Connection technology           | CAGE CLAMP®                       |
| Actuation type                  | Operating tool                    |
| Connectable conductor materials | Copper                            |
| Solid conductor                 | 0.08 ... 2.5 mm² / 28 ... 14 AWG  |
| Fine-stranded conductor         | 0.08 ... 2.5 mm² / 28 ... 14 AWG  |
| Strip length                    | 8 ... 9 mm / 0.31 ... 0.35 inches |
| Pole number                     | 11                                |
| Wiring direction                | Side-entry wiring                 |

| Connection 2     |             |
|------------------|-------------|
| Actuation type 2 | Push-button |



| Physical data           |                        |
|-------------------------|------------------------|
| Width                   | 69 mm / 2.717 inches   |
| Height from the surface | 23.3 mm / 0.917 inches |
| Depth                   | 28.1 mm / 1.106 inches |
| Module width            | 6 mm / 0.236 inches    |

| Mechanical data |                 |
|-----------------|-----------------|
| Design          | horizontal type |
| Mounting type   | Snap-in foot    |
| Marking level   | Side marking    |

| Material data               |                                                                                                                        |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------|
| Note (material data)        | <a href="https://www.wago.com/us/material-specifications">Information on material specifications can be found here</a> |
| Color                       | gray                                                                                                                   |
| Material group              | I                                                                                                                      |
| Insulation material         | Polyamide (PA66)                                                                                                       |
| Flammability class per UL94 | V0                                                                                                                     |
| Fire load                   | 0.615 MJ                                                                                                               |
| Halogen-free                | Yes                                                                                                                    |
| Weight                      | 28.2 g                                                                                                                 |

| Commercial data       |               |
|-----------------------|---------------|
| eCl@ss 10.0           | 27-14-11-06   |
| eCl@ss 9.0            | 27-14-11-06   |
| ETIM 8.0              | EC001284      |
| ETIM 7.0              | EC001284      |
| PU (SPU)              | 25 pcs        |
| Packaging type        | Box           |
| Country of origin     | DE            |
| GTIN                  | 4045454722883 |
| Customs tariff number | 85369010000   |

| Environmental Product Compliance |                         |
|----------------------------------|-------------------------|
| RoHS Compliance Status           | Compliant, No Exemption |

Approvals / Certificates

| General approvals               |          |                  | Declarations of conformity and manufacturer's declarations |          |                  |
|---------------------------------|----------|------------------|------------------------------------------------------------|----------|------------------|
|                                 |          |                  | Approval                                                   | Standard | Certificate Name |
| Approval                        | Standard | Certificate Name | EU-Declaration of Confor- mity<br>WAGO GmbH & Co. KG       | -        | -                |
| CCA<br>DEKRA Certification B.V. | EN 60998 | NTR-NL 6509      | UK-Declaration of Confor- mity<br>WAGO GmbH & Co. KG       | -        | -                |
| CCA<br>DEKRA Certification B.V. | EN 60998 | 2110272.02       |                                                            |          |                  |



Approvals for marine applications



| Approval                                | Standard | Certificate Name |
|-----------------------------------------|----------|------------------|
| ABS<br>American Bureau of Ship-<br>ping | -        | 19-HG1869868-PDA |

Downloads

Environmental Product Compliance

| Compliance Search                                      |
|--------------------------------------------------------|
| Environmental Product<br>Compliance<br>261-161/331-000 |



Documentation

| Additional Information                 |
|----------------------------------------|
| Technical Section<br>pdf<br>2240.62 KB |



| Bid Text                                         |
|--------------------------------------------------|
| 261-161/331-000<br>19.02.2019<br>xml<br>3.15 KB  |
| 261-161/331-000<br>17.08.2017<br>doc<br>25.00 KB |



CAD/CAE-Data

| CAD data                        |
|---------------------------------|
| 2D/3D Models<br>261-161/331-000 |



| CAE data                             |
|--------------------------------------|
| EPLAN Data Portal<br>261-161/331-000 |
| WSCAD Universe<br>261-161/331-000    |
| ZUKEN Portal<br>261-161/331-000      |



1 Compatible Products

1.1 Optional Accessories

1.1.1 DIN-rail

1.1.1.1 Mounting accessories



Item No.: 210-154  
Aluminum carrier rail; 1000 mm long; 18 mm wide; 7 mm high; silver-colored



1.1.2 Ferrule

1.1.2.1 Ferrule

|                                                                                                                                      |                                                                                                                                      |                                                                                                                                       |                                                                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
|                                                     |                                                     |                                                      |                                                    |
| <p><b>Item No.: 216-301</b><br/>Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; insulated; electro-tin plated; yellow</p>          | <p><b>Item No.: 216-321</b><br/>Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; insulated; electro-tin plated; yellow</p>          | <p><b>Item No.: 216-151</b><br/>Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated</p>                 | <p><b>Item No.: 216-131</b><br/>Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated; silver-colored</p> |
|                                                     |                                                     |                                                      |                                                    |
| <p><b>Item No.: 216-302</b><br/>Ferrule; Sleeve for 0.34 mm<sup>2</sup> / 22 AWG; insulated; electro-tin plated; light turquoise</p> | <p><b>Item No.: 216-322</b><br/>Ferrule; Sleeve for 0.34 mm<sup>2</sup> / 22 AWG; insulated; electro-tin plated; light turquoise</p> | <p><b>Item No.: 216-132</b><br/>Ferrule; Sleeve for 0.34 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated</p>                 | <p><b>Item No.: 216-152</b><br/>Ferrule; Sleeve for 0.34 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated</p>                 |
|                                                     |                                                     |                                                      |                                                    |
| <p><b>Item No.: 216-201</b><br/>Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; insulated; electro-tin plated; white</p>            | <p><b>Item No.: 216-221</b><br/>Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; insulated; electro-tin plated; white</p>            | <p><b>Item No.: 216-101</b><br/>Ferrule; Sleeve for 0.5 mm<sup>2</sup> / AWG 22; uninsulated; electro-tin plated; silver-colored</p>  | <p><b>Item No.: 216-121</b><br/>Ferrule; Sleeve for 0.5 mm<sup>2</sup> / AWG 22; uninsulated; electro-tin plated; silver-colored</p>  |
|                                                     |                                                     |                                                      |                                                    |
| <p><b>Item No.: 216-202</b><br/>Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; gray</p>            | <p><b>Item No.: 216-222</b><br/>Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; gray</p>            | <p><b>Item No.: 216-102</b><br/>Ferrule; Sleeve for 0.75 mm<sup>2</sup> / AWG 20; uninsulated; electro-tin plated; silver-colored</p> | <p><b>Item No.: 216-122</b><br/>Ferrule; Sleeve for 0.75 mm<sup>2</sup> / AWG 20; uninsulated; electro-tin plated; silver-colored</p> |
|                                                     |                                                     |                                                      |                                                    |
| <p><b>Item No.: 216-203</b><br/>Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; red</p>                | <p><b>Item No.: 216-223</b><br/>Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; red</p>                | <p><b>Item No.: 216-103</b><br/>Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; uninsulated; electro-tin plated</p>                    | <p><b>Item No.: 216-123</b><br/>Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; uninsulated; electro-tin plated; silver-colored</p>    |
|                                                   |                                                   |                                                    |                                                  |
| <p><b>Item No.: 216-204</b><br/>Ferrule; Sleeve for 1.5 mm<sup>2</sup> / AWG 16; insulated; electro-tin plated; black</p>            | <p><b>Item No.: 216-224</b><br/>Ferrule; Sleeve for 1.5 mm<sup>2</sup> / AWG 16; insulated; electro-tin plated; black</p>            | <p><b>Item No.: 216-124</b><br/>Ferrule; Sleeve for 1.5 mm<sup>2</sup> / AWG 16; uninsulated; electro-tin plated</p>                  | <p><b>Item No.: 216-104</b><br/>Ferrule; Sleeve for 1.5 mm<sup>2</sup> / AWG 16; uninsulated; electro-tin plated; silver-colored</p>  |
|                                                   |                                                   |                                                    |                                                                                                                                       |
| <p><b>Item No.: 216-205</b><br/>Ferrule; Sleeve for 2.08 mm<sup>2</sup> / AWG 14; insulated; electro-tin plated; yellow</p>          | <p><b>Item No.: 216-206</b><br/>Ferrule; Sleeve for 2.5 mm<sup>2</sup> / AWG 14; insulated; electro-tin plated; blue</p>             | <p><b>Item No.: 216-106</b><br/>Ferrule; Sleeve for 2.5 mm<sup>2</sup> / AWG 14; uninsulated; electro-tin plated; silver-colored</p>  |                                                                                                                                       |

1.1.3 Installation

1.1.3.1 Mounting accessories

|                                                                                                  |                                                                                                                                                                   |
|--------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|               |                                                                                |
| <p><b>Item No.: 209-137</b><br/>Mounting adapter; can be used as end stop; 6.5 mm wide; gray</p> | <p><b>Item No.: 209-120</b><br/>Mounting foot; can be snapped on terminal blocks with snap-in mounting foot; for mounting on relay-modules; 6.4 mm wide; gray</p> |

1.1.4 Jumper

1.1.4.1 Jumper



**Item No.: 261-402**  
Jumper; for conductor entry; 2-way; insulated; gray

1.1.5 Marking

1.1.5.1 Marking strip



**Item No.: 210-833**  
Marking strips; 25 m on roll; 6 mm wide; plain; Self-adhesive; white

1.1.6 Tool

1.1.6.1 Operating tool



**Item No.: 210-658**  
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; angled; short; multicoloured




**Item No.: 210-720**  
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured




**Item No.: 210-657**  
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; short; multicoloured

Installation Notes

Conductor termination




**CAGE CLAMP® connection**  
Inserting a conductor.  
With ferruled conductors, it is necessary to use a terminal block one size larger than the conductor's nominal cross-section.



**CAGE CLAMP® connection**  
Inserting a conductor via push-button.

Commoning



Commoning with comb-style jumper bar.


Installation




Mounting a terminal strip with snap-in feet into holes.




Mounting a terminal strip with snap-in feet onto aluminum rail.



Terminal strip with snap-in mounting feet  
Snapping a mounting foot (209-120).  
(Distance between mounting feet: approx. 25 ... 30 mm)



Terminal strip; with snap-in mounting feet;  
for DIN-35 rail



Terminal strip with snap-in mounting feet,  
for 0.6 ... 1.2 mm plate thickness, 3.5 mm  
mounting hole diameter (also for 210-154  
Aluminum Rail or with 209-120 Mounting  
Foot for DIN-35 rail)

Marking



Marking with self-adhesive marking strips.



Marking by direct printing (upon request).