

Smart double switch, screw fixing

410-00210

4 year warranty

Mechanism for a smart double switch, with screw fixing. A finishing set and faceplate in the colour of your choice must be ordered separately.

Technical data

Smart double switch, screw fixing.

- Not compatible with the wireless bridge
- LED colour: white
- Maximum MCB rating: 16 A (limited by national installation rules)
- Communication protocol: Easywave
- Maximum radio frequency power: 5 dBm
- Operating frequency: 0.8683 GHz
- Flush-mounting frame
 - 1 mm-thick metal
 - galvanized on all sides after cutting, even on the cut edges
 - with 4 grooves with screw hole of 7 mm
 - with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm for mounting on panels
- Flush mounting depth: 27.5 mm
- Required type of flush-mounting box
 - depth: min. 40 mm (cabling space included)
 - claw/screw fixing: 60 mm
 - inner diameter box: 60 mm
 - multiple boxes centre distance horizontal: 71 mm
 - multiple boxes centre distance vertical: 71 mm
 - multiple boxes centre distance vertical: 60 mm for Belgium and France
- Fixing method
 - with screws for simple fixing in a flush-mounting box with grip surfaces
- Dimensions (HxWxD): 71.2 x 73.2 x 41.5 mm
- Weight: 84 g
- Marking: CE

