

## 43P-161516: T-piece Press 16 x compression 15 x Press 16



### Commercial information

- Direct connection to Henco press 16 mm in copper or central heating pipe 15 mm
- Short installation length 2 x Press 16 mm x Compression 15 mm

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 49 mm    |
| Length     | 95 mm    |
| Width      | 26 mm    |
| Net weight | 0.139 kg |

#### Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, EMI

#### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

|                                    |                                                |                                  |                        |
|------------------------------------|------------------------------------------------|----------------------------------|------------------------|
| Material connection 1              | Brass                                          | Angle                            | 90 Degrees             |
| Surface protection connection 1    | Untreated                                      | Outer pipe diameter connection 1 | 16 Millimetre          |
| Surface treatment connection 1     | Untreated                                      | Outer pipe diameter connection 2 | 15 Millimetre          |
| Material connection 2              | Brass                                          | Outer pipe diameter connection 3 | 16 Millimetre          |
| Surface protection connection 2    | Untreated                                      | Wrench width                     | 0 Millimetre           |
| Surface treatment connection 2     | Untreated                                      | Max. operating pressure at 20 °C | 16 Bar                 |
| Material connection 3              | Brass                                          | Wrench width union nut           | 0 Millimetre           |
| Surface treatment connection 3     | Untreated                                      | Medium temperature (continuous)  | -10 70 Degrees celsius |
| Model                              | T-piece                                        | Standard Dimension Ratio (SDR)   | 0                      |
| Reducing                           | ✗                                              |                                  |                        |
| System specific                    | ✓                                              |                                  |                        |
| Connection 1                       | Press sleeve                                   |                                  |                        |
| Connection 2                       | Compression ring                               |                                  |                        |
| Connection 3                       | Press sleeve                                   |                                  |                        |
| Material sealing                   | Ethylene-propylene diene monomer rubber (EPDM) |                                  |                        |
| Main colour fitting                | Brass                                          |                                  |                        |
| High tensile strength              | ✗                                              |                                  |                        |
| Ring stiffness class               | Other                                          |                                  |                        |
| With sealing rings/gaskets         | ✓                                              |                                  |                        |
| With drain valve                   | ✗                                              |                                  |                        |
| With de-aerator                    | ✗                                              |                                  |                        |
| With thermal insulation            | ✗                                              |                                  |                        |
| With buffer stud                   | ✓                                              |                                  |                        |
| Capped                             | ✗                                              |                                  |                        |
| FM quality mark                    | ✗                                              |                                  |                        |
| LPCB quality mark                  | ✗                                              |                                  |                        |
| ULC quality mark                   | ✗                                              |                                  |                        |
| UL quality mark                    | ✗                                              |                                  |                        |
| DIN-CERTCO certificate             | ✗                                              |                                  |                        |
| VdS quality mark                   | ✗                                              |                                  |                        |
| With approval for TÜV              | ✗                                              |                                  |                        |
| DVGW quality mark for gas          | ✗                                              |                                  |                        |
| DVGW quality mark for water        | ✓                                              |                                  |                        |
| KIWA certified                     | ✓                                              |                                  |                        |
| Gastec QA mark                     | ✗                                              |                                  |                        |
| KOMO certified                     | ✓                                              |                                  |                        |
| Type approval according to BBR/EKS | ✗                                              |                                  |                        |