


VDEK-T05: T-connection piece - 2x eurocone



Commercial information

T-adapter for Henco PVDF manifold

- for water or as extra outlet
- Henco threaded connector
- 2 eurocone connectors (top and bottom) – can also be used as water supply
- Positioning aligned perpendicular to the manifold
- Compact solution for installations with limited installation space
- Makes it possible to add an air vent connector to the manifold

Basic unit dimensions

Height	30 mm
Length	60 mm
Width	45 mm
Net weight	0.031 kg

Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Angle	90 Degrees
Surface protection connection 1	Untreated	Max. operating pressure at 20 °C	16 Bar
Surface treatment connection 1	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Material connection 2	Polyvinylidene fluoride (PVDF)		
Surface protection connection 2	Untreated		
Surface treatment connection 2	Untreated		
Material connection 3	Polyvinylidene fluoride (PVDF)		
Model	T-piece		
Swept entry type (with inner radius)	✗		
Reducing	✗		
System specific	✓		
Connection 1	Insert (push-fitting)		
Connection 2	Other		
Connection 3	Euroconus (expired)		
Flange standard	Other		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	White		
High tensile strength	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✗		
With drain valve	✗		
With de-aerator	✗		
With buffer stud	✗		
Capped	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		