


Concord

Rocks IP65 40KLM 840 AISLE DALI EM
2825467



Features

- Logistics and Industry high bay luminaire with Aisle optics to provide necessary illumination for narrow areas, comes complete with 2000mm flying lead and 1000mm suspension cable, aluminium housing, PC diffuser, IP65, IK08, Class I, 4000K, CRI80, 3 step MacAdam ellipse, DALI dimmable, Integrated 3hrs Self Test Emergency LiFePO4 unit, 40800lm, 226W, 181lm/W, 105.000hrs L80B50 lifespan, 446 x 963 x 138mm (LxWxD) dimensions, 11.097kg weight, RAL7012 Basalt Grey color, 0...+40°C operating temperature range. Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3.

Product Overview

Product name	Rocks IP65 40KLM 840 AISLE DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	40800
Luminaire efficacy (lm/W)	181
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	60
Glare control	< 22
Photobiological Risk Group	RG1

Concord

Rocks IP65 40KLM 840 AISLE DALI EM 2825467

Luminous flux (emergency) (lm)	800
Total power consumption (W)	226
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5025768254675
Warranty	5 years
Dimming method	DALI-2

Photometry

Technical drawings

