

Technical Sheet

Code

4060452779



Product description URINAL FRAME 135 IR 9 V

Commercial description (product) Urinal elements, which enable comfortable and hygienic use with contact free activation based on infra-red sensor.

- Technical description (product)
- Installation in prefabricated walls, pre-wall installation in dry walls, universal installation into solid walls
 - Supporting, blue powder coated urinal element, square profile 40 x 40 mm
 - Pre-mounted fixing elements and flexible support legs (0-200 mm)
 - Height adjustable bracket for mounting urinals
 - Height adjustable bracket for urinal support
 - Height adjustable plate with a brass angle connector
 - Height adjustable and rotating drain elbow Ø 50 mm
 - Rough installation set (ID 223761) for installation of IR set with stainless metal flushing plate HALITE for urinals, battery (ID 229581)
 - M8 threaded rod (285 mm distance)
 - Metal tube Ø 20/20 mm with a Ø 20 mm connecting elbow
 - All parts required for mounting and fixing of the product
 - Without a concealed trap

Product Classification Characteristics

| | | | |
|--|-----------------|--|-------------------------|
| Material | Steel | Height | 1350 1550 Millimetre |
| Self-bearing construction | Yes | Width | 380 380 Millimetre |
| Suitable for drywall | Yes | Depth | 135 200 Millimetre |
| Suitable for solid wall | No | Outer pipe diameter drainage | 50 Millimetre |
| Suitable for sanitary installation wall system | No | Connection voltage | 9 Volt |
| Surface protection | Coated | Max. pre-pressure | 4 Pressure |
| Adjustable height | Yes | Min. pre-pressure | 1.2 Pressure |
| Adjustable width | No | Pre-pressure | 1.2 4 Pressure |
| Adjustable depth | Yes | Number of attachment points according to element | 4 |
| Adjustable urinal height | Yes | | |
| Tap water connection | Internal thread | | |
| Size of tap water connection | 1/2 inch | | |
| With drainage bend | Yes | | |
| Battery power supply | Yes | | |
| Flushing time usage frequency adjustment | No | | |
| Programmable with remote control | No | | |
| With pre-flushing | No | | |
| With building management system connection | No | | |
| Adjustable throughflow capacity | Yes | | |
| Pre-assembled flushing unit | Yes | | |
| Suitable for manual operation | No | | |
| Suitable for manual operation | No | | |
| Suitable for pneumatic operation | No | | |
| Suitable for radar operation | No | | |
| Suitable for infrared operation | Yes | | |
| Pre-assembled element | Yes | | |
| With inlet fittings | Yes | | |
| With mounting material for the element | Yes | | |
| With urinal attachment materials | Yes | | |
| With spacer tube for radar antenna | No | | |
| With siphon | No | | |

KIWA certified
KIWA certified

No
No

Accessories

| Product code | Description |
|--------------|---|
| 382881 | IR-URINAL-CONTROL, BATTERY POWER SUPPLY, 9 V |
| 382879 | ROUGH INSTALLATION KIT, BATTERY POWER SUPPLY, 9 V |
| 229581 | HALITE, IR FLUSHING PLATE FOR URINALS, BATTERY, 9 V |
| 8090390500 | URINAL SEPARATION PANEL |

