

## Beacon LED XL

### BEACON XL 93CRI 3K WIDE BEAM L3 WHITE

#### 2059689



#### Product features

- Integrated LED spotlight, white RAL 9016, compact and minimalist design, ideal for retail, display, museum and gallery applications, die-cast aluminium body, passive cooling heatsink, beam angle: 50° wide beam, optics: Polycarbonate lens, colour temperature: 3000K warm white, total system power: 33W, total fixture output: 2802lm, luminaire efficacy: 85lm/W, LOR: 100%, colour rendering: Ra 93 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 800mA, electronic driver, non-dimmable, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø113x165x205mm, weight: 1.66kg.




#### PRODUCT OVERVIEW

Product name	BEACON XL 93CRI 3K WIDE BEAM L3 WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Museums & Galleries, Retail
ETIM Class	EC001744
E-number FI	4280849
Warranty	5 years
Useful luminous flux (Fuse)	2802
Fixture luminous flux (lm)	2802
Luminaire efficacy (lm/W)	85
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	93
Colour Consistency (SDCM)	3
Beam Angle (°)	50
Photobiological Risk Group	RG1
Total power consumption (W)	33
Electrical protection	Class II
Control gear type	Electronic ballast
Dimmable	No
Dimming method	N/A
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768596898

## Beacon LED XL BEACON XL 93CRI 3K WIDE BEAM L3 WHITE 2059689

### PHOTOMETRY



0.5	0.43	507 5100	1002 6492
1.0	0.87	507 5100	982 1998
1.5	1.30	507 5100	666 1332
2.0	1.73	507 5100	495 981
2.5	2.16	507 5100	392 774
3.0	2.60	507 5100	301 602

Distance [m] Cone diameter [m]  
C0 - C180 (Half beam angle: 46.8°) Illuminance [lx]

### TECHNICAL DRAWINGS

