



Wide range of surface-mounting and flush-mounting boxes for domestic ranges with high mechanical robustness and accessories supplied: dividers, junction elements, mortarguard shield, etc. Completing the range, the distribution outlet boxes for floor-mounting installations can be personalised in terms of capacity, external design finish, and internal fittings (they take both System range components and DIN rail devices).

| | | | |
|-----------------------------------|------------------------------------|---|---------------------------|
| In overeenstemming met normen | EN 60670-1, EN 60670-23, CEI 23-48 | Installatie temperatuur | -5 ÷ +45 °C |
| Compatibility with domestic range | SYSTEM | Degree of protection underfloor outlet box edge/floor | IP52 |
| Interne modulariteit | 10 SYSTEM-modules | Degree of protection cover/underfloor outlet box interior | IP40 (IP20 cable opening) |
| Aant. steunen | 2 steunen met 5 System mod. | Gloeidraadtest | 850 °C |
| Buitenste afm. LxHxD (mm) | 212 x 98 x 320 | Resistance to point load (N) | 500 |
| Materiaal | GW PLAST Technopolymer | Resistance to distributed load (N) | 1000 |
| Halogeenvrij | Halogeenvrij conform EN 60754-2 | | |

TECHNICAL SYMBOLOGY



850 °C

STANDARDS/APPROVALS

