

Locknuts - LNZ Series



Type LNZ

Technical specification

Plating: Electroless Nickel, Zinc, other on application

Part number: Please refer to page 10 for part numbering system

Features

- Available in brass, mild steel, stainless steel, aluminium and nylon 6
- Various threadforms available

Benefits

- Provides a method for securing a threaded entry component into a piece of equipment

Materials

- Brass CZ121
- 316 stainless steel
- Aluminium
- Mild steel
- Nylon 6

Threadforms

- Metric
- NPT
- NPSM
- PG
- ISO pipe (BSP)
- ET

Earthing locknuts - LEZ Series



Type LEZ

Technical specification

Plating: Electroless nickel, zinc

Part number: Please refer to page 10 for part numbering system

Dimensions of metric versions

Size	A/F
M12	14.00
M16	18.00
M20	23.00
M25	28.00
M32	36.00
M40	44.00
M50	54.00
M63	70.00

Features

- Available in brass and stainless steel
- Metric and NPT threadforms available

Benefits

- An alternative method of earthing when terminating metallic cable glands into a thin steel wall enclosure
- Cutting teeth on one surface cut into enclosure on tightening, securing the nut

Materials

- Brass CZ121
- 316 Stainless steel

Threadforms

- Metric
- NPT