




Color: ■ light green

Similar to illustration

Technical data	
Marking method	Thermal transfer
Marking	PE
Marking (number)	100
Marking direction	Horizontal marking
Marking color	black
Marking type	Symbol
Marking layout	Same symbols per strip
Delivery form	Marker card
Delivery form configuration	10 strips with 10 markers per card
Flammability class per UL94	V2

Physical data	
Marker/strip width	5 mm
Marker width	5 mm

Mechanical data	
Smear resistance	EN 60998-1:2004

Material data		
Color		light green
UV resistance		EN 60068-2-5:2010 Procedure B
Halogen-free		Yes
Weight		9 g
Fire load		0.27 MJ

Commercial data		
Product Group		2 (Terminal Block Accessories)
PU (SPU)		50 (5) pcs
Packaging type		Box
Country of origin		DE
GTIN		4044918029551
Customs tariff number		49119900000

Product Classification		
UNSPSC		55121718
eCl@ss 10.0		27-14-11-37
eCl@ss 9.0		27-14-11-37
ETIM 9.0		EC000761
ETIM 10.0		EC000761
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption


Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 793-578/000-017	

Installation Notes

Application



Separating a strip from the WMB or WMB marker card.	Stretching a WMB marker strip.	Separating an individual marker from the WMB marker strip – for larger terminal blocks.	Snapping a marking strip into the marker slot.
---	--------------------------------	---	--

Marking



Snapping a WMB marker strip into the marker slot of the double marker carrier.



Snapping a marking strip into the marker slot.