

## Product data sheet

Item No. 91.222.2004.2

### Cable assembly GST15I2KS-S 15 W 20WS

geis® Connection cable male - free end; length: 2m; type GST15I2; 2-pole; 250 V / 16 A; colour of coding: white with white strain-relief; cable: H05VV-F 2x1,5, colour: white



|            |               |
|------------|---------------|
| Item No.   | 91.222.2004.2 |
| EAN        | 4015573924611 |
| Order Unit | 50 Piece(s)   |

## Certificates / Approvals

### Technical data

#### General

|                                          |        |
|------------------------------------------|--------|
| Rated current                            | 16 A   |
| Rated voltage                            | 250 V  |
| Rated impulse voltage                    | 4 kV   |
| Pollution degree                         | 2      |
| Mechanical coding                        | Code 1 |
| Interlockable                            | Yes    |
| Color of coding/ contact carrier         | White  |
| Marking of poles                         |        |
| Color of housing inclusive strain relief | White  |

#### Model

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Number of poles                 | 2                                   |
| Nominal cross section conductor | 1.5 mm²                             |
| Degree of protection (IP)       | IP40                                |
| Wire strip length               | 8 mm                                |
| sheath strip length             | 21 mm                               |
| Preparation of conductor ends   | Ultrasonically compressed wire ends |
| Cable type                      | H05VV-F                             |
| Cable colour                    | White                               |
| Cable diameter                  | 7.5 mm                              |

|                     |                  |
|---------------------|------------------|
| Version of cable    | Male - free end  |
| Type of cord set    | Connection cable |
| Version cable end 1 | GST15i2 plug     |
| Version cable end 2 | Free end         |

**Material**

|                                              |               |
|----------------------------------------------|---------------|
| Surface finish                               | Silver-plated |
| Halogen free                                 | No            |
| Continuous temperature of cable              | 70 °C         |
| Insulation components continuous temperature | 100 °C        |

**Dimensions**

|              |     |
|--------------|-----|
| Total length | 2 m |
|--------------|-----|