

Fivefold faceplate with 71 mm centre-to-centre distance Niko Pure alu steel grey

226-76005

4 year
warranty

Fivefold faceplate with 71 mm centre-to-centre distance from the range Niko Pure. Finishing colour faceplate: Niko Pure alu steel grey

Technical data

Fivefold faceplate with 71 mm centre-to-centre distance Niko Pure alu steel grey.



- Fivefold faceplate for five switches.
- Colour: alu steel grey (approximately NCS S 8005 - R80B, RAL 240 30 05)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made of anodised aluminium (alu grey).
- Material lower frame: grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), blue grey coated
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 367 x 8.9 mm
- Marking: CE

CE