

## TESTPLUG16-RO: Test cap, red, for pipe Ø26



### Commercial information

- Suitable for pressing Henco Tubes according to the guidelines mentioned in our technical manual
  - Sanitary installations
  - Heating installations
  - Gas installations
  - Compressed air installations
- Suitable for
  - Henco Multilayer 16mm and 20mm until 15 bar
  - Henco 5L Pert 16mm and 20mm until 6 bar
  - Henco 5L PEXc 16mm and 20mm until 6 bar
- Easy to use
- Not suitable as a final, long-lasting solution. Max use of 3 months under a pressure of 10 bar.
- Not reusable

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 21 mm    |
| Length     | 14 mm    |
| Width      | 14 mm    |
| Net weight | 0.003 kg |

#### Certificates

#### Applications

Potable water, Heating, Compressed air, Gas, Underfloor Heating, Sanitary

#### Solutions

Building installations, Industry, Underfloor heating, Oil & gas, Utility

Technical characteristics

|                             |         |                           |                  |
|-----------------------------|---------|---------------------------|------------------|
| Material                    | Plastic | For nominal tube diameter | 16 16 Millimetre |
| Suitable for rigid tubes    | ✓       |                           |                  |
| Suitable for flexible tubes | ✓       |                           |                  |
| Suitable for pliable tubes  | ✓       |                           |                  |
| Colour                      | Red     |                           |                  |