

ToLEDo Superia T8 UNIVERSAL

ToLEDo Superia T8 Universal V3 5FT 3600LM 840

0029277



Product features

- 50,000 hours average rated life Last 2.5 times longer than 1500mm 58W fluorescent T8 Tri-phosphor lamp
- High switching cycles - 200,000X
- High lumen efficacy - 157lm/W
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 50°C
- Glass construction and polycarbonate end-caps
- Works only with compatible electronic ballast
- Must replace the fluorescent starter with LED dummy starter when used with magnetic/ CCG ballast
- Suitable for direct mains operation (AC 220-240V) with single-end AC input
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices



PRODUCT OVERVIEW

Product name	ToLEDo Superia T8 Universal V3 5FT 3600LM 840
Technology	LED
Watt (Rated) (W)	23
Lamp shape	Tube, double-ended
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4940797
Warranty	5 years
Useful luminous flux (Fuse)	3600
Luminous flux (lm)	3600
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	160
Photobiological Risk Group	RG0
Power consumption (W)	23
Wattage (W)	23
Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20
Product EAN number	5410288292779

PHOTOMETRY

ToLEDo Superia T8 UNIVERSAL

ToLEDo Superia T8 Universal V3 5FT 3600LM 840
0029277

