

ToLEDo Superia T5 ECG

ToLEDo Superia T5 ECG HO V3 5FT 5600LM 840

0029271

Product features

- 50,000 hours average rated lifetime
- Last 2.5 times longer than 80W 1449mm fluorescent tri-phosphor T5 lamp
- High switching cycles - 200,000X
- High lumen efficacy
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 50°C
- Glass construction and polycarbonate end-caps
- Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast
- Works only with compatible electronic ballasts
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices




PRODUCT OVERVIEW

Product name	ToLEDo Superia T5 ECG HO V3 5FT 5600LM 840
Technology	LED
Watt (Rated) (W)	37
Lamp shape	Tube, double-ended
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4940793
Warranty	5 years
Useful luminous flux (Fuse)	5600
Luminous flux (lm)	5600
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Power consumption (W)	37
Wattage (W)	37
Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20
Product EAN number	5410288292717

PHOTOMETRY

ToLEDo Superia T5 ECG

ToLEDo Superia T5 ECG HO V3 5FT 5600LM 840
0029271



TECHNICAL DRAWINGS

