

ToLEDo Superia T5 AC

ToLEDo Superia T5 AC V2 4FT 2400LM 840

0029256

Product features

- 50,000 hours average rated lifetime
- Last 2.5 times longer than 28W 1149mm fluorescent tri-phosphor T5 lamp
- High switching cycles - 200,000X
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 50°C
- Glass construction and polycarbonate end-caps
- Only suitable for direct mains (AC 220-240V) operation
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices
- Not suitable for operation with electronic/ECG or magnetic/CCG ballasts




PRODUCT OVERVIEW

Product name	ToLEDo Superia T5 AC V2 4FT 2400LM 840
Technology	LED
Watt (Rated) (W)	16
Lamp shape	Tube, double-ended
Type	LED exchangeable
Cap/Base	G5
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4940788
Warranty	5 years
Luminous flux (lm)	2400
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Wattage (W)	16
Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20
Product EAN number	5410288292564

PHOTOMETRY

ToLEDo Superia T5 AC

ToLEDo Superia T5 AC V2 4FT 2400LM 840
0029256



TECHNICAL DRAWINGS

