

ToLEDo Superia T5 AC

ToLEDo Superia T5 AC V2 5FT 2800LM 840

0029258

Product features

- 50,000 hours average rated lifetime
- Last 2.5 times longer than 35W 1449mm fluorescent tri-phosphor T5 lamp
- High switching cycles - 200,000X
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 50°C
- Glass construction and polycarbonate end-caps
- Only suitable for direct mains (AC 220-240V) operation
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices
- Not suitable for operation with electronic/ECG or magnetic/CCG ballasts




PRODUCT OVERVIEW

Product name	ToLEDo Superia T5 AC V2 5FT 2800LM 840
Technology	LED
Watt (Rated) (W)	18.5
Lamp shape	Tube, double-ended
Cap/Base	G5
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4940790
Warranty	5 years
Useful luminous flux (Fuse)	2800
Luminous flux (lm)	2800
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Power consumption (W)	18.5
Wattage (W)	18.5
Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20
Product EAN number	5410288292588

PHOTOMETRY

ToLEDo Superia T5 AC

ToLEDo Superia T5 AC V2 5FT 2800LM 840
0029258



TECHNICAL DRAWINGS

