

## ToLEDo Superia T5 AC

ToLEDo Superia T5 AC V2 4FT 2400LM 840  
0029256

### Product features

- 50,000 hours average rated lifetime
- Last 2.5 times longer than 28W 1149mm fluorescent tri-phosphor T5 lamp
- High switching cycles - 200,000X
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 50°C
- Glass construction and polycarbonate end-caps
- Only suitable for direct mains (AC 220-240V) operation
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices
- Not suitable for operation with electronic/ECG or magnetic/CCG ballasts




## PRODUCT OVERVIEW

Product name	ToLEDo Superia T5 AC V2 4FT 2400LM 840
Technology	LED
Watt (Rated) (W)	16
Lamp shape	Tube, double-ended
Cap/Base	G5
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4940788
Warranty	5 years
Useful luminous flux (Fuse)	2400
Luminous flux (lm)	2400
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Power consumption (W)	16
Wattage (W)	16
Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20
Product EAN number	5410288292564

## PHOTOMETRY

## ToLEDo Superia T5 AC

ToLEDo Superia T5 AC V2 4FT 2400LM 840  
0029256



## TECHNICAL DRAWINGS

