




Color: ■ orange

Similar to illustration

Technical data		
Suitable		for decade marking (with red printing)
Marking method		Thermal transfer
Marking		210, 220 ... 300
Marking (number)		10
Marking direction		Vertical marking
Marking color		red
Marking type		Numbers
Marking layout		Same numbers per strip
Delivery form		Marker card
Delivery form configuration		10 strips with 10 markers per card
Flammability class per UL94		V2

Physical data		
Marker/strip width		5 mm
Marker width		5 mm

Mechanical data		
Smear resistance		EN 60998-1:2004

Material data	
Color	orange
UV resistance	EN 60068-2-5:2010 Procedure B
Halogen-free	Yes
Weight	9 g
Fire load	0.27 MJ

Commercial data	
Product Group	2 (Terminal Block Accessories)
PU (SPU)	50 (5) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332720908
Customs tariff number	49119900000

Product Classification	
UNSPSC	55121731
eCl@ss 10.0	27-14-11-37
eCl@ss 9.0	27-14-11-37
ETIM 9.0	EC000761
ETIM 8.0	EC000761
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption


Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 793-657/000-012	

Installation Notes

Application



Separating a strip from the WMB or WMB marker card.	Stretching a WMB marker strip.	Separating an individual marker from the WMB marker strip – for larger terminal blocks.	Snapping a marking strip into the marker slot.
---	--------------------------------	---	--

Marking



Snapping a WMB marker strip into the marker slot of the double marker carrier.



Snapping a marking strip into the marker slot.

Marking



WMB "decade" marking