

Specifications

Eaton BSPMA3480WYGR

Eaton Bussmann series BSPM series surge arrestor, Technology type MOV, 277/480 V, Surge arrestor, Thermoplastic, UL94V2, 50/60 Hz, 200 Kilo Ampere, Thermoplastic, Remote Contact

General specifications

PRODUCT NAME	Eaton Bussmann series BSPM series surge arrestor
CATALOG NUMBER	BSPMA3480WYGR
UPC	051712709095
PRODUCT LENGTH/DEPTH	2.13 in
PRODUCT HEIGHT	3.54 in
PRODUCT WIDTH	2.56 in
PRODUCT WEIGHT	0.73 lb
WARRANTY	Five year limited warranty
COMPLIANCES	Contact factory RoHS Compliant
CERTIFICATIONS	UL 94V0 UL Listed
PRODUCT TYPE	Surge arrestor

Product specifications

FREQUENCY RATING	50/60 Hz
NOMINAL DISCHARGE CURRENT	20 kA
OPERATING VOLTAGE	550
VOLTAGE RATING	277/480 V
ENCLOSURE	Thermoplastic, UL94V2
SURGE CURRENT	200 kA
INDICATOR TYPE	Remote contact
SHORT-CIRCUIT RATING	200 kA
OPERATING TEMPERATURE	-35 to 85 °C
MOUNTING METHOD	35 mm DIN rail
DEGREE OF PROTECTION	IP20
MATERIAL	Thermoplastic
TYPE	Surge arrestor
SPECIAL FEATURES	Technology type MOV
APPLICATION	Surge Protection

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007
	BSPMA3480WYGR~277/480 Wye, 3P
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BSPMA3480WYGR

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

