# Product data sheet Spirotech

## Product name

**EVU6 Expansion vessel, 6 bar - 12L, hanging**

## Article number

**EVU6-12**

## Product properties


Safety expansion vessels with replaceable membrane, P max. 6 bar / T max. 70ºC.

- Tested according to Pressure Equipment Directive 2014/68/EU
- Max. temperature at connection point: 70 degrees
- Max. operating pressure: 6 bar
- Allowed system medium: water or water/glycol mixture min. 25% / max. 50%
- Unique 5-year warranty period for vessels ≤140L
- 2-year warranty period for vessels >140L

## Product image




## Product dimensions



# Product data sheet Spirotech

## ETIM product data

| | |
|---|---|
| **Height** | 278 mm |
| **Volume** | 12 l |
| **Colour** | Other |
| **Diameter** | 305 mm |
| **Medium temperature (continuous)** | -10 - 70 °C |
| **Max. operating pressure** | 6 bar |
| **Connection** | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) |
| **With exchangeable membrane** | Yes |
| **Nominal diameter expansion connection** | DN 15 |
| **Outer pipe diameter, expansion connection** | 20.9 mm |
| **Horizontal positioning** | Yes |
| **Suitable for central heating** | Yes |
| **Vertical positioning** | Yes |
| **With legs** | No |
| **Material membrane/bladder** | Ethylene-propylene diene monomer rubber (EPDM) |
| **With vessel manifold** | Yes |
| **With drain** | Yes |
| **Tilting height** | 307 mm |
| **With mounting material** | Yes |
| **Max. glycol mixture** | 50 % |
| **Suitable for tap water** | No |
| **Suitable for solar collector circuit** | Yes |
| **Pre-pressure** | 3.5 bar |
| **With fixed wall support** | Yes |
| **Suitable for cooling** | Yes |

**Disclaimer**
This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website