

Double 2-pole socket outlet without earthing, complete device incl. faceplate, white

101-67410

$\frac{16 \text{ A}}{250 \text{ V}_{\text{ac}}}$



Double 2-pole flush-mounting socket outlet, 16 A/250 Vac, with faceplate. The double socket outlet fits in 1 single flush-mounting box. The faceplate is attached to the socket outlet with screws. Complete device incl. faceplate and pre-assembled finishing set. Colour: white.

Technical data

Double 2-pole socket outlet without earthing, complete device incl. faceplate, white.

- Colour: white
- Colour RAL (approximately): 9010
- Colour NCS (approximately): NCS S 0502-Y50R
- Surface treatment: coloured in mass
- Type of earthing: without earthing
- Nominal voltage: 250 V
- Flush-mounting frame type:
 - 1 mm-thick metal
 - galvanized on all sides
 - with 4 grooves
- Material finishing: rigid polycarbonate (PC)
- Type of fastening:
 - with screws for simple fixing in a flush-mounting box with grip surfaces
- Terminals location: top of the base
- Terminal wire connection: screw terminals
- Terminals wire capacity: 4 x 2.5 mm²
- Fire safety:
 - all plastic components are self-extinguishing (comply with a filament test of 650°C)
 - all plastic components are halogen-free
- Halogen-free: yes
- Minimum ambient temperature: -5 °C
- Maximum ambient temperature: 40 °C
- Protection degree standalone: IP20
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20



- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Marking: CE

Wiring diagram

