


Concord

BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE WHITE 2059669



Features

- Integrated LED spotlight, white RAL 9016, compact and minimalist design, ideal for retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 55° wide beam, optics: Aluminium reflector, colour temperature: 3000K warm white, total system power: 21W, total fixture output: 2208lm, luminaire efficacy: 105lm/W, LOR: 100%, colour rendering: Ra 85 typical, LED Chromacity: 3 step MacAdam ellipse, lifetime: >72,000 hours at L80B50, energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, trailing edge dimmable, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø80x130x190mm, weight: 0.96kg.

Product Overview


Product name	BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
E-number FI	4280819
E-number SE	7401246
Fixture luminous flux (lm)	2208
Luminaire efficacy (lm/W)	105
LOR (%)	100

Concord

BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE WHITE 2059669

Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	85
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	21
Electrical protection	Class II
Control gear type	Electronic ballast
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768596690
Warranty	5 years


Photometry



Concord

BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE WHITE 2059669

Technical drawings



Data table

GENERAL DATA

Product name	BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
Performance ambient temperature Tq (°C)	25
E-number FI	4280819
E-number SE	7401246
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2208
Luminaire efficacy (lm/W)	105
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	85
Colour Consistency (SDCM)	3

Concord

BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE WHITE 2059669

Adjustable chromaticity	N
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	21
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.9
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast
Drive current (mA)	500
Inrush Current (A)	45
Inrush Duration (µs)	20
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	48

LIFETIME DATA

Lifespan L70 B50	72000
Lifespan L70 B10	72000
Lifespan L80 B50	72000
Lifespan L80 B20	72000
Lifespan L80 B10	72000
Lifespan L90 B50	43000
Lifespan L90 B20	36000
Lifespan L90 B10	33000

PHYSICAL DATA

Housing colour	White
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	70

Concord

BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE WHITE 2059669

Nominal Product Width (mm)	130
----------------------------	-----

Weight (kg)	0.7
-------------	-----

PACKAGING

Single packaging type	Carton
-----------------------	--------

Product EAN number	5025768596690
--------------------	---------------

Packaging single width (cm)	17.6
-----------------------------	------

Packaging single depth (cm)	18.2
-----------------------------	------

DUN14 (outer)	05025768596690
---------------	----------------

Packaging outer length / height (cm)	16.0
--------------------------------------	------

SAFETY DATA

Special purpose lamp	No
----------------------	----

Dry applications use only	No
---------------------------	----

Suitable for household illumination	No
-------------------------------------	----