ETHERMA°
EFFICIENT. ELECTRIC. HEATING.

PRODUCT DATASHEET

Type: ET-DUO-PLUS-S2-1500-W
Art. Nr.: 46728

9120129934909

Short description
Convector storage heater, stone, white, 1500W, 230V





Product Description
The ETHERMA DUO PLUS S2 convector storage heater is a modern direct heating device with an innovative combination of convection, radiant heat, and integrated heat storage. This triple heating technology ensures efficient heat distribution, shortens heating times, and optimizes energy consumption at the same time. Thanks to its compact design, the unit is ideal as space-saving transitional heating or as a modern replacement for outdated night storage heaters – especially in large rooms. It is mounted horizontally on the wall and connected via a 1 m long connection cable with plug. The DUO PLUS S2 has a function switch with three operating modes: Off, operation without internal control (for external eco-design-compliant room thermostats) and operation with internal control. In normal operation, the device offers additional comfort functions such as window open detection with automatic switch-off and individually adjustable daily and weekly programs. When the control is switched off, an integrated frost protection mode is active at 7°C. The surface consists of 12 mm thick, coated silicon stone, which radiates heat evenly. Protection class: IP 24. Control range: 15–28 °C. Surface temperature: max. 85 °C. Mounting depth: 105 mm. Operating voltage: 230 V. The system is CE-compliant and offers a reliable, intelligent solution for modern direct heating systems.

ETIM 10 Characteristics

Model	Standard	**Heating capacity**	1500	Watt
Mounting method	On wall	**Supply voltage**	230|230	Volt
Material front	Other	**Frequency supply voltage**	50|50	Hertz
Grid model	Fins	**Connection cable length**	1	Metre
Material heating element	Other	**Number of switch positions**	1	
Air exhaust	Top side	**Temperature adjustment**	15|28	Degrees celsius
With fan	✖	**Differential gap, temperature**	0.1	Degrees celsius
Electrical connection	Connection cable with plug	**Width**	1000	Millimetre
Position control panel	Top side	**Height**	500	Millimetre
Suitable for wireless remote control	✖	**Depth**	105	Millimetre
With remote control	✖	**Weight**	22	Kilogram
Power control	Electronic			
Colour	White			
Degree of protection (IP)	IP24			
Protection class according to IEC 61140	II			
With overheating protection	✔			
Programmable	✔			
Frost protection circuit	✔			
Digital indication	✔			
With presence detector	✖			
Suitable for bus connection	✖			
With time switch clock	✔			
Adaptive (self-learning)	✖			
Consumption indication	✖			
Open window detection	✔			

Created on: 14/09/2026

ETHERMA Elektrowärme GmbH
Landesstrasse 16
A-5302 Henndorf am Wallersee
Tel.: +43 6214 / 76 77
Mail: office@etherma.com
Web: www.etherma.com

ETHERMA Deutschland GmbH
Bahnhofstraße 40
D-48599 Gronau
Tel.: +49 2562 / 81 97 00
Mail: office.de@etherma.com
Web: www.etherma.com

Compatible with Apple HomeKit	✖
Compatible with Google Assistant	✖
Operation by app	✖
Compatible with Amazon Alexa	✖
IFTTT support available	✖
Number of supported pilot wire commands	None